File
(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER M-1-294 Relating to Certification of New Motorcycles

KAWASAKI HEAVY INDUSTRIES, LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and,

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Kawasaki Heavy Industries, Ltd. exhaust emission control systems are certified as described below for four-stroke gasoline-powered motorcycles:

Engine Family	Displacement Cubic Centimeters	Class	Exhaust Emission Control Systems & Special Features
YKAXC.899AAB	899	III	Pulsed Secondary Air Injection Oxidation Catalytic Converter

Vehicle models and transmissions are listed on the attachment. Production motorcycles shall be in all material respects the same as those for which certification is granted.

The following are the exhaust emission standards and exhaust emission certification values for this engine family. The designated hydrocarbons standard shall be listed on the permanent tune-up label:

Hydrocarbon St	tandards	Hydrocarbons	Carbon M	Monoxide
(Corporate Average)				
Grams per Kilometer				
1.4	0.7	0.4	12	2

BE IT FURTHER RESOLVED: That the above-described certification is subject to the following terms, limitations and conditions:

The above designated hydrocarbons standard shall be the exhaust limit for this engine family during the model year and therefore cannot be redesignated by the manufacturer. It represents the hydrocarbons exhaust emission standard applicable to this engine family that shall be applied when determining compliance of any motorcycle within this engine family pursuant to Section 2101 of Title 13, California Code of Regulations. It will also be used to determine compliance with the above corporate average hydrocarbons standard as required per Section 1958(b), Title 13 of the California Code of Regulations.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That these motorcycles are found exempt from compliance with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 8

_ day of September 1999.

R. B. Summerfield, Chief

Mobile Source Operations Division

E. O. H: M-1-294 Section: 7: Page: 6 Issued: AUG 1 3 333

Revised:

Engine Family: YKAXC.899AAB

Motorcycle Model Summary Form

65. Model Designation	66. Worst Case	67. Disp. (cc)	68. Bore	69, Basic Ignition	70 Power (kW)	71 Rated Speed	72 Rated Torque	73. Rated Speed
			Stroke (mm)	Timing (degrees)		(RPM)	(Nm)	(RPM)
ZX900-C3	Yes	899	75.0X50.9	10°/1100 rpm	104	11000	100	9000
ZX900-E1	4-1	899	75.0X50.9	10°/1100 rpm	105	11000	101	9200

65. Model Designation	74. EIM (kg)	75. Loaded Vehicle Weight Range (kg)	76 Road Load (nt)	77 Total Vehicle Mass (kg)	78 Full Weight with All Factory Options (kg)	79. Trans. Type	80 N/V
ZX900-C3	340	340	143.6	210	265	M-6	41.09
ZX900-E1	340	340	143.6	212	265	M-6	41.09

E.O. #: M-1-294

Section: 7: Page: 1 Issued: AUG 1 0 1999

Revised:

Motorcycle Engine Family Information Form

2. Certification Co	ontact Person, address, phone	, and fax:		
Jeffrey D.Shetle Kawasaki Moto	er / Scott Patten ors Corp., U.S.A. Road, Irvine, CA 92618-2		2	
3. Model Year: _2	2000	10.	Displacement: _	899 cm ³
4. Process Code:	New_ection, r/c, f/f. etc.)	11.	Number of Cylind	lers: <u>4</u>
	•	12.	Cylinder Arranger	ment: <u>Inline-4</u>
5. Engine Family: 50s Engine 49s Engine		13.	Cylinder Head Co	nfiguration: <u>DOHC</u>
	ne Code: ZX900C-AC1	14.	Type of Cooling:	Liquid
6. Emission Cont	rol System: <u>EM+PAIR+OC</u>	2 15.	Combustion Cycle	e: <u>4</u>
7. Calif. Designat	red Standard: 0.7gm/km	16.	Method of Aspira	tion: Natural
8. Projected Annu	ual Sales: _450	17.	Fuel System: Ca	rhuretor
		17.	ruor oysteini. <u>-ca</u>	Tourctor
O. New Technolog If yes, cite the c submittal docu	y Yes _X_ No correspondence or reference to the same of the sa	18.		tic Converters: 2
O. New Technolog If yes, cite the consumment of	y Yes _X_ No correspondence or reference to the timent:	18.	Number of Cataly	tic Converters: 2
9. New Technolog If yes, cite the o	y Yes _X_ No correspondence or reference to the same of the sa	18.		
9. New Technolog If yes, cite the c submittal docu	y Yes X No correspondence or reference to the same of	Tamper I	Number of Cataly	tic Converters: 2
New Technolog If yes, cite the consumption of the submittal documents of th	y Yes X No correspondence or reference to the same of	Tamper I	Number of Cataly Resistance Method (or NA) num cap is placed	tic Converters: 2 Method Approved
D. New Technolog If yes, cite the consumption of th	y Yes X No correspondence or reference to the same of	Tamper I an alumi over the	Number of Cataly Resistance Method (or NA) num cap is placed adjusting screw.	tic Converters: 2 Method Approved
New Technolog If yes, cite the consumption of the submittal documents of th	y Yes _X No correspondence or reference to the same of the sam	Tamper I an alumi over the Evap	Number of Cataly Resistance Method (or NA) num cap is placed adjusting screw.	Method Approved Carry over
D. New Technolog If yes, cite the consumption of th	y Yes X No correspondence or reference to the same of	Tamper I an alumi over the Evap	Number of Cataly Resistance Method (or NA) num cap is placed adjusting screw.	tic Converters: 2 Method Approved

Application Processed by: Joseph Jegede Date: 9/8/99
Reviewed by: Steven Hade Date: 9/8/99

Revised:

Engine Family: YKAXC.899AAB

Motorcycle Test Information Form

a) b)	If yes, indicate family name: <u>WKAXC</u> . Is the family being certified identical to the	899AA	[2] [3] [3] [4] [4] [4] [4] [4] [4] [4] [4] [4] [4
28. Model Desi	gnation of Test Vehicle: ZX900-C1	36.	Road Load: 143.6 nt at 65 kph
29. Test Inform	ation Number: 98-1	37.	Inertia Mass: 340 kg
30. Vehicle ID	D: JKAZX2C1XWA000006	38.	N/V: 41.09
31. Service Acc	eumulation Duration: 15000 (km)	39.	EVAP. Bench Test Method Approved: Date: _6/21/1985_
32. Maximum F	Rated Power: <u>104</u> kW @ <u>11000</u> RPM		Reference: _EO M-1-61_
33. Displacemen	nt: <u>899</u> cc		
34. Certification	Fuel: Indolene: 91-95 RON	40.	Unscheduled Maintenance: Yes _X_ No

41. If yes, Vehicle Log provided:

42. Exhaust Emission Deterioration Factors:

35. Test Data Set: Test 1

		Emissi	on Values
Test Number	System Kilometers	HC	CO
1	3512	0.51	1.3
2	6012	0.47	1.9
3	6101	0.42	1.0
4	12012	0.45	1.1
5	12101	0.45	0.9
6	15012	0.39	1.7
7 *1	15084	0.57	1.6
8 *2	15114	0.59	1.6

Regular DF	X
Modified DF	
f different vehic	le
specify vehicle I	D

Interpolated Values at 15000 km: $HC = 0.4103 \quad CO = 1.2592$ Extrapolated Values at 30000 km: $HC = 0.3132 \quad CO = 1.2404$

*1 This emission test was performed in order to confirm the previous EPA's approval test data which was submitted in 1998 model year certification.

*2 This emission test was performed with new parts(Air cleaner, Cab, ICM) and using fuel of 95-99 RON.

43. Emission Test Results:

Official Test Results		Test 1	Test 2	Test 3	Test 4
g/km	СО	1.7			/
g/km	CO ₂	157.1			
g/km	НС	0.39			
g/test	Evap.	0.721			

	Deterioration Factors
(X)	1.000
(X)	1.000
(+)	0.095

44.

g/km	СО	(2)	-
g/km	HC	0.4		
g/test	Evap.	0.816		

E.O. #: M-1-294 Section: 7:

Issued: AUG 1 n 1999

Revised:

Engine Family: YKAXC.899AAB

Evaporative Emission Information

- 45. Evaporative Family: YKAXC17.0A04
- 46. Number of Evap, Canisters: 1
- Design Working Capacity: 17.0 g 47.
- 48. Configuration: Sealed loop
- 49. Number of Storage Areas: 1
- Fuel Reservoir Volume: 4.4 liters 50.
- Vent System Configuration: Sealed loop 51.
- 52. Nominal Tank Capacity: 19 liters

- 53. Engine Displacement Class: III
- 54. Storage Medium Composition: Activated carbon
- 55. Evap. Canister Medium Volume: 400cm³
- 56. Evap. Family Sales: 950
- 57. Engine Code: ZX900A-AC1 **** Bench test ZX750F-AC1 **** Durability test
- 58. Evap. Emission Family Code: YKAXC17.0A04
- 59. Evap. Emission Family Group: CVK34-004
- 60. Overall Evap D.F. = _0.095 •Evap certification level = 0.816 g/test

Bench DF

- 61. Test Vehicle ID: JKAZX2A12EA000048
- 62. Test Results:

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3500	1.101
2	15000	1.246
3		
4		
5		
6		
7		
Interpolated Va	lues at <u>15000</u> km	= 1.246
Extrapolated V	alues at 30000 km	n: = <u>1.4351</u>
Bench Test D.F	. = _0.189_	

Regular DF:	X
Modified DF:	
If different vehicespecify the vehice	

- Test Vehicle ID: JKAZXDF15HA000019
- Test Results.

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3266	1.136
2	5040	1.089
3	5070	0.994
4	10113	0.994
5	10143	0.902
6	15012	0.721
7		
Interpolated Va	ilues at 15000 km:	= _0.7579

Extrapolated Values at 30000 km: = 0.2905

Vehicle Test D.F. = 0.000