

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-13-16
Relating to Certification of New Motor Vehicle Engines

CATERPILLAR TRACTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by Sections 43100 and 43102 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That Caterpillar Tractor Company 1977 model-year diesel-powered engines in heavy-duty motor vehicles are certified for the engine family described below:

<u>Engine Family</u>	<u>Engine Size (CID)</u>	<u>Engine Model</u>	<u>Type</u>
10	893	3406	Inline six - Turbocharged-Aftercooled

Section 43200, Part 5, Division 26 of the California Health and Safety Code requires that the manufacturer affix a decal to the side window to the rear of the driver or, if there is no such window on the driver's side, to the windshield of the motor vehicle.

The decal shall display the applicable model year heavy-duty engine exhaust emission standards and the following recommended values:

<u>Engine Family</u>	<u>HC + NOx gm/bhp-hr</u>	<u>CO gm/bhp-hr</u>	<u>HC gm/bhp-hr</u>	<u>NOx gm/bhp-hr</u>
10	Not applicable	1	0.3	5

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 17 day of December, 1976.

G. C. Hass
G. C. Hass, Chief
Vehicle Emissions Control Division

1977 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET HEAVY-DUTY DIESEL ENGINES

Manufacturer Caterpillar Tractor Co. Executive Order No. A-13-16 Page 1Engine Family 10 Engine (CID) 893Emission Control Systems _____ Type Inline six-turbocharger-aftercooler

Engine Model	Fuel Pump Mfgr. Part Number	Injector Mfg. Part Number	Maximum Rated HP and RPM	Fuel Rate at Maximum HP	Basic Initial Timing
3406	Caterpillar 9N72	Caterpillar 4N1251	375 HP @ 2100 RPM 360 HP @ 2100 RPM 340 HP @ 1950 RPM	211 mm ³ /stroke 150 lbs/hr 197 mm ³ /stroke 140 lbs/hr 200 mm ³ /stroke 131.9 lbs/hr	10° BTDC (static)
Comments					
Date of Issue					
Abbreviation Type					

NA - Natural Aspiration

TC - Turbocharged

TCA- Turbocharged and Aftercooled