

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-27-25
Relating to Certification of New Motor Vehicle Engines

MACK TRUCKS, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That the following Mack Trucks, Inc. 1979 model-year diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating greater than 8500 pounds:

<u>Engine Family</u>	<u>Displacement Cubic Inches</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
10	998	V-8 Turbocharged, Aftercooled

Engine Models and Codes as listed on attachments.


Section 43200, Part 5, Division 26 of the California Health and Safety Code requires that the engine manufacturer furnish a decal with each engine sold or delivered to a vehicle manufacturer. The decal shall display the applicable model year heavy-duty engine exhaust emission standards and the following certification emission values:

<u>Engine Family</u>	<u>Hydrocarbons gm/bhp-hr</u>	<u>Carbon Monoxide gm/bhp-hr</u>	<u>Nitrogen Oxides gm/bhp-hr</u>	<u>Hydrocarbons + Nitrogen Oxides gm/bhp-hr</u>
10	0.2	1	5.7	NA

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 2 day of February, 1979.



G. C. Hass, Chief
Vehicle Emissions Control Division

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
HEAVY-DUTY DIESEL ENGINES

Manufacturer MACK TRUCKS, INC.

Page 1

Engine Family 10

Engine (CID) 998

Emission Control Systems Acceleration Smoke
Puff Limiter

Type 8 Cylinder "V"

Engine Model	Fuel Injection Pump Mfgr. Part Number	Injector Mfg. Part Number Nozzle Part #	Maximum Rated HP and RPM	Fuel Rate at Maximum HP $\frac{mm^3}{stroke}$	Basic Initial Timing
Thermodyne ETAX (B) 1000	American Bosch 313GCA- 5133-P10	American Bosch 114GC39-P10	400 @ 1900 RPM	221.8	13° BTDC Fixed
Maxidyne ETAX (B) 1005A	American Bosch 313GCA- 5133-P6		392 @ 2100 RPM		

Date of Issue -

Abbreviations

Type

NA - Natural Aspiration

TC - Turbocharged

TCA - Turbocharged and Aftercooled

Emission Control Systems

AC - Aftercooler

EGR - Exhaust Gas Recirculation

TD - Throttle Delay