

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAM	IILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6				
				Dual-Fuel:	PROCEDURE	CLASS	ECM, TWC, 2HO2S, SFI	N/A				
2009	9BAFE06.89CH		6.8	HCNG or CNG	Otto	HDO		1 '*"				
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL		ADDITIONAL IDLE EMISSIONS CONTROL 5										
	N/A	N/A										
ENGINE (L)	ENGINE MODELS / CODES (rated power, in hp)										
6.8		V-10 / BAF0968H (231)										
*												
*		*										
L=liter; hp: CNG/LI HCNG=Hyd L/M/H F BCS=er up catalyst; Super charg control mod ESS=er (per 13 CC)	-horsepower; kw=ki MG=compressed/liqu drogen and compress IDD=light/medium/he nission control syste DPF=diesel particu body fuel injection; per; CAC=charge air fule; EM=engine mo ignie shutdown syste R 1956.8(a)(6)(D);	lowatt; hrefied natura sed natura sety heavy m; TWC/C late filter; SFI/MFI=: cooler; E dification; em (per 13 exempt=ex	=hour; ral gas; LPG=liquefie; gas blend. γ-duty diesel; UB=url DC=three-way/oxidzii PTOX=periodic trap i sequential/multi port; GR / EGR-C=exhaus 2 (prefix)=psaralel; (CCR 1956.8(a)6(b./k) (cmpted per 13 CCR	d petroleum gas; E85=85% ett pan bus; HDO=heavy duty Otto ng catalyst; NAC=NOx adsorpt soxidizer; HO2S/O2S=heated/ox uel injection; DGI=direct gasoli t gas recirculation / cooled EGF 2) (suffix)=in series; (1); 30g=30 g/hr NOx (per 13 d	nanol fuel; MF=mult c; ion catalyst; SCR-U kygen sensor; MAFS ne injection; GCAR t; PAIR/AIR=pulsed CCR 1956.8(a)(6)(C G fuel systems; N/A	/ SCR-N=select // SCR-N=select // SCR-N=select // SER-N=select	1. 86.abc=Title 40, Code of Federal Regulation bi fuel; DF=dual fuel; FF=flexible fuel; tive catalytic reduction → urea / → ammonia; ir-fuel-ratio sensor (a.k.a., universal or linear unretor, IDI/DDI=indirect/direct diesel injectionjection; SPL=smoke puff limiter; ECM/PCA (combustion auxiliary power system; ALT=1 (e.g., Otto engines and vehicles);	WU (prefix) =warm- oxygen sensor); n; TC/SC=turbo/ f=engine/powertrain				

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on CNG. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		co		PM		нсно	
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14 [0.14]	*	0.20 [0.20]	*	*	*	14.4 [14.4]	*	0.01 [0.01]	*	0.01 [0.01]	*
FEL	*	*	*	*	*	*	*	*		*	•	*
CERT	0.04 [0.07]	*	0.06 [0.05]	*	*	•	6.2 [6.9]	*	0.003 [0.01]	* .	0.003 [0.000]	*
NTE	*		*		Ŕ		*		*		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro til European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

,

day of July 2009.

Annette Hebert, Chief

Mobile Source Operations Division