## **BAYTECH CORPORATION**

EXECUTIVE ORDER A-330-0212 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL. YEAR	ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6			
, LAK				Dual-Fuel:	PROCEDURE	CLASS	2TWC, SFI, 2HO2S	EMD			
2009	9BYTE08.1C23 8.1		8.1	CNG or Gasoline	Otto HD		21110, 011, 211020				
	MARY ENGINE'S IDLE ISSIONS CONTROL  ADDITIONAL IDLE EMISSIONS CONTROL										
	N/A				N/A						
ENGINE (	INE (L) ENGINE MODELS / CODES (rated power, in hp)										
8.1		GM 8.1L / 1 (283 CNG / 317 Gasoline)									
L=liter; hp:  CNG/LN L/WH F ECS=er up catalyst; TBI=throttle super charg control mod ESS=er	=horsepower; kw=k NG=compressed/liqu IDD=light/medium/hum mission control syste ; DPF=cliesel particu, a body fuel injection; ger; CAC=charge al dule; EM=engine mo- ngine shuldown systi	ilowatt; hi efied natu eavy heav em; TWC/ ilate filter; SFI/MFI= r cooler; E idification; em (per 13	=hour; ral gas; LPG=liquefi y-duty diesel; UB=u 0C=three-way/oxidiz PTOX=periodic trap sequential/multi port GR / EGR-C=exhau 2 (prefix)=parallel; CCR 1956.8(a)(6)(c)	ied petroleum gas; E85=85% ethir rban bus; HDO=heavy duty Otto; bing catalyst; NAC=NOx adsorptio oxidizer; HO2s702s=heated/oxy, fuel injection; DGI=direct gasolin ist gas recirculation / cooled EGR; (2) (suffix)=in series; Ay(1); 30g=30 g/hr NOx (per 13 C	anol fuel: MF=mult on catalyst; SCR-U gen sensor; HAFs e injection; GCAR PAIR/AIR=pulsec CR 1958.8(a)(6)(C	i fuel a.k.a. BF / SCR-N=select //AFS=heated/a B=gaseous car //secondary air ); APS=intema	R 86.abc=Title 40, Code of Federal Regulation  =bi fuel; DF=dual fuel; FF=flexible fuel;  citive catalytic reduction – urea / – ammonia; \u00e4  air-fuel-ratio sensor (a.k.a., universal or linear  buretor; IDVDDI=indirect/direct diesel injection injection; SPL=semoke puff limiter; ECMPC  al combustion auxiliary power system; ALT=a	WU (prefix) =warm- oxygen sensor); n: TC/SC=turbo/ M=engine/powertrain			
(per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);											

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		со		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
\$TD	+	*	*	*	*	*	14.4 (14.4)	*	0.01 (0.01)	*	0.01 (0.01)	*
FEL	0.16 (0.16)	*	0.35 (0.35)	*	*		*	*	*	*	*	*
CERT	0.000 (0.13)	*	0.30 (0.16)	*	*	*	2.1 (2.7)	*	0.001 (0.001)	*	0.001 (0.002)	*
NTE	*		+		*		, *		+		+	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

**BE IT FURTHER RESOLVED:** Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 30 day of March 2009.

Annette Hebert, Chief
Mobile Source Operations Division