

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAM	iLY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE 2	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6
2009	9CEXH0505	CAC	8.3	Diesel	PROCEDURE Diesel	MHDD	DDI, TC, CAC, ECM, EGR, OC, PTOX, SCR	EMD
PRIMARY E	ENGINE'S IDLE IS CONTROL		0.0		TIONAL IDLE EN		5	
ENGINE (L)				ENGINE MODE	LS / CODES (ra	ted power, in	hp)	
8.3				See attachmen	t for engine me	odels and ra	atings	
*					*			***************************************
*	1				*			
*					*			
L=liter; hp=h CNG/LNG L/M/H HD ECS=emi	horsepower; kw=k G=compressed/liqu DD=light/medium/h ission control syste DPF=diesel particu	ilowatt; hi efied natu eavy heav m; TWC/ late filter;	r=hour; iral gas; LPG=liquef ry-duty diesel; UB=u OC=three-way/oxidiz PTOX=periodic trap	ied petroleum gas; E85=85% eth rban bus; HDO=heavy duty Otto; ing catalyst; NAC=NOx adsorptio oxidizer, HO2S/O2S=heated/ox	anoi fuel; MF=mult on catalyst; SCR-L ygen sensor; HAF:	i fuel a.k.a. BF I / SCR-N=sele S/AFS=heated/	R 86.abc=Title 40, Code of Federal Regulations =bi fuel; DF=dual fuel; FF=flexible fuel; ctive catalytic reduction – urea / – ammonia; W air-fuel-ratio sensor (a.k.a. universal or linear o buretor; IDI/DDI=indirect/direct diesel injection;	'U (prefix) =warm- xygen sensor);

control module; EM=engine modification; 2 (preffx)=parallel; (2) (sufffx)=in series;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NM	нс	N	Ox	NMH	C+NOx	C	:0	P	M	н	СНО
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	*	*	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	0.38	0.38	0.38	0.38	*	*	*	*	*	*
CERT	0.00	0.00	0.18	0.15	0.18	0.15	0.0	0.0	0.001	0.000	*	*
NTE	0.2	21	0	.57	0.	.57	19	9.4	0.	02		*

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of December 2009.

Annette Hebert, Chief Mobile Source Operations Division

Engine Model Summary Template #Hachmen, page 10/1

EO#: A-021-0515

Date: 12/03/2009 ENG

				4.Fuel Rate:	5.Fuel Rate:		7.Fuel Rate:	i L		
Family	1.Engine Code	Engine Family 1.Engine Code 2.Engine Model	3.BHP@RPM (SAE Gross)	mm/stroke @ peak HP (lbs/hr) @ peak HP 6.Torque @ RPM (for diesel only) (SEA Gross)	(lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	8.Fuel Kate: 9.Emission Control (Ibs/hr)@peak torqueDevice Per SAE J1930	
505CAC	9CEXH0505CAC 3092;FR92521 ISC8.3 380	ISC8.3 380	352@2200	175	130	1050@1400	203	96	SCRC, PTOX	
3505CAC	9CEXH0505CAC 3093,FR92584 ISC8.3 350	ISC8.3 350	320@2200	164	122	1000@1400	195	92	scrk, Ptox,	
0505CAC	9CEXH0505CAC 3093;FR92579 ISC8.3 330	ISC8.3 330	320@2200	164	122	1000@1400	195	92	scrc, KTOX,	
0505CAC	9CEXH0505CAC 3093;FR92581 ISC8.3 300	ISC8.3 300	285@2200	150	111	860@1300	162	7	scac, Prox,	
0505CAC	9CEXH0505CAC 3093FR92582	ISC8.3 270	260@2200	137	102	800@1300	155	89	scrc, PTOX,	
3505CAC	9CEXH0505CAC 3093;FR92523	ISC8.3 260	260@2200	137	102	660@1300	128	56	SCRC, PTOX,	

J chi ch