EXECUTIVE ORDER A-021-0494 New On-Road Heavy-Duty Engines Page 1 of 1 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

| MODEL<br>YEAR   | ENGINE FAN   | ENGINE FAMILY  |   | FUEL TYPE <sup>1</sup>  | STANDARDS<br>& TEST   | INTENDED<br>SERVICE  | ECS & SPECIAL FEATURES 3   | DIAGNOSTIC 6   |  |  |
|---|--|--|---|---|---|--|--|--|--|--|
| 2009 9CEXH0540LAO   |  | 8.9  | Diesel  | PROCEDURE   | UB  | DDI, TC, CAC, ECM, EGR, OC,<br>PTOX  | EMD  |  |  |  |
| EMISSIO   | ENGINE'S IDLE NS CONTROL XEMPT   |  |   | ADDI  | TIONAL IDLE EN  | issions coi  | NTROL 5  |  |  |  |
| 8.9   |  |  |   |   |   |  |  |  |  |  |
| CNG/LN L/M/H HI ECS=err up catalyst; rBl=throttle super charge control mode ESS=eng | G=compressed/liqu DD=light/medium/he hission control syste DPF=diesel particul body fuel injection; er, CAC=charge air ule; EM=engine mo pine shutdown syste | efied nature<br>avy heavy<br>m; TWC/(<br>late filter;<br>SFVMFI=;<br>cooler; E<br>dification;<br>m (per 13 | rai gas; LPG=iquefi<br>/-duty diesel; UB=un<br>DC=three-way/oxidiz<br>PTOX=periodic trap<br>sequential/multi port<br>GR / EGR-C=exhau<br>2 (prefix)=parallel;<br>CCR 1956 8/a/6/4 | ed petroleum gas; E85=85% ethi<br>ban bus; HDO=heavy duty Otto;<br>ing catalyst; NAC=NOx adsorptic<br>oxidizer; HO2S/O2S=heated/oxy<br>fuel injection; DGH=direct gasolin<br>st gas recirculation / cooled EGR;<br>12) [sufffx]=n series; | anol fuel; MF=multi<br>n catalyst; SCR-U<br>gen sensor; HAFS<br>e injection; GCARI<br>PAIR/AIR=pulsed | fuel a.k.a. BF= / SCR-N=selecti/AFS=heated/a B=gaseous cart /secondary air I | R 86.abc=Title 40, Code of Federal Regulations =bi fuel; DF=dual fuel; FF=flexible fuel;  tive catalytic reduction – urea / – ammonia; Wi iir-fuel-ratio sensor (a.k.a., universal or linear os buretor; IDI/DDI=indirect/direct diesel injection; njection; SPL=smoke puff limiter; ECMIPCM= il combustion auxiliary power system; ALT=alte | U (prefix) ≃warm-<br>(ygen sensor);<br>TC/SC≃turbo/<br>engine/powertrain |  |  |

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on ponventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in

| in<br>g/bhp-hr | NMHC |      | NOx  |      | NMHC+NOx |      | CO   |      | PM    |       | нсно   |      |
|----------------|------|------|------|------|----------|------|------|------|-------|-------|--|------|
|                | FTP  | EURO | FTP  | EURO | FTP      | EURO | FTP  | EURO | FTP   | EURO  | FTP  | EURO |
| \$TD           | 0.14 | 0.14 |      | •    | *        | *    | 15.5 | 15.5 | 0.01  | 0.01  | -  | *    |
| FEL            | *    | +    | 1.25 | 1.25 | 1.2      | 1.2  | *    | *    | *     | *     |  | ļ    |
| CERT           | 0.03 | 0.00 | 1.02 | 0.85 | 1.05     | 0.85 | 0.9  | 0.00 | 0.002 | 0.000 | *  | *    |
| NTE            | 0.21 |      | 1.88 |      | 1.8      |      | 19.4 |      | 0.02  |       | <del>                                     </del> |      |

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions lesting; NTE=Noi-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

**BE IT FURTHER RESOLVED:** The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

\_ day of February 2009.

Annette Hebert, Chief

Mobile Source Operations Division