GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1572-1 New On-Road Heavy-Duty Engines Page 1 of 1 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1 Gasoline	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC ⁶ EMD		
					PROCEDURE	CLASS T	2TWC, 2HQ2S(2), SFI			
2009	9GMXE04.8	GMXE04.8581 4			Otto	HDO	21110, 211020(2), 011			
	PENGINE'S IDLE	_		ADD	ITIONAL IDLE EN	IISSIONS CO	NTROL ⁵			
N/A		N/A								
ENGINE (INE (L) ENGINE MODELS / CODES (rated power, in hp)									
4.8	4.8 LY2 / 40 (264); L20 / 45 (264)									
L=liter; hp CNG/Li L/M/H is ECS=e up catalyst TBI=throttil super chan control mode ESS=e {per 13 CC	ambrespower; kiw=k NG=compressed/liquid HDD=light/medium/h mission control syste; DFF=diesel particle body fuel injection; ger; CAC=charge al dule; EM=engine mongine shutdown system R 1956.8(a)(6)(D);	ilowatt; hr lefied nature eavy heavy lefier; TWC/0 sFl/MFl= r cooler; E odification; em (per 13 Exempt=e	=hour; ral gas; LPG=liquef y-duty diesel; UB=u OC=three-way/oxidiz PTOX=periodic trap sequential/multi port cGR / EGR-C=exhau 2 (praffx)=parallel; c CCR 1956.8(a)(6), kempted per 13 CCI	ed petroleum gas; E85=85% eth rban bus; HDO=heavy duty Otto ing catalyst; NAC=NOx adsorptioxidizer; HO2S/O2S=heated/ox fuel injection; OBI=direct gasolist gas recirculation / cooled EGR (2) (suffix)=in series; A(1); 30g=30 g/hr NOx (per 13 0)	nanol fuel; MF=multi; on catalyst; SCR-L tygen sensor; HAF, ne injection; GCAR t; PAIR/AIR=pulser CCR 1956.8(a)(6)(C G fuel systems; N/A	i fuel a.k.a. BF J / SCR-N=seler S/AFS=heated// B=gaseous car d/secondary air ;; APS =intern. =not applicable	R 86.abc=Title 40, Code of Federal Regulatio =bi fuel; DF=dual fuel; FF=flexible fuel; ctive catalytic reduction – urea / – ammonia; air-fuel-ratio sensor (a.k.a., universal or linear buretor; IDI/DDI=indirect/direct diesel injectio injection; SPL=smoke puff limiter; ECM/PCA al combustion auxiliary power system; ALT=a a (e.g., Otto engines and vehicles);	WU (prefix) =warm- oxygen sensor); n: TC/SC=turbo/ H=engine/powertrain		

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		CO		PM		HCHO	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	*	*	*	-*	. *	*	14.4	*	0.01	*	0.01	
FEL	0.28	*	0.68	*		*	*	+	*	*	*	*
CERT	0.14	*	0.52	*	*	*	5.1	+	*	*	0.001	*
NTE	*		*		*		*		•		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1572 dated May 30, 2008.

Executed at El Monte, California on this 2.3 day of December 2008.

✓ Annette Hebert, Chief

Mobile Source Operations Division