

parentheses.).

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6			
YEAR				·	PROCEDURE	CLASS 2	DDI, TC, CAC, ECM, EGR, OC,				
2010	ACEXH0408	EXH0408BAL 6.7		Diesel	Diesel	MHDD_	PTOX, SCR-U				
	'ENGINE'S IDLE NS CONTROL	ADDITIONAL IDLE EMISSIONS CONTROL 5									
	30g N/A										
ENGINE (	L)	ENGINE MODELS / CODES (rated power, in hp)									
6.7		ISB6.7 305 / 2786;FR92396 (305), ISB6.7 305 / 2791;FR92411 (305)									
*											
*		*									
*		<del></del>									
L=liter, hp: CNG/LN L/M/H F	=horsepower; kw=k NG=compressed/liqu IDD=light/medium/h	ilowatt; <b>hr</b> efied natu eavy heav	≔hour; ral gas; LPG=liquef y-duty diesel; UB≕u	ied petroleum gas; E85=85% eth irban bus; HDO=heavy duty Otto;	anol fuel; MF=mult	ifuela.k.a. BF	R 86.abc=Title 40, Code of Federal Regulation: =bi fuel; DF=dual fuel; FF=flexible fuel; ctive catalytic reduction – urea / – ammonia; W				

control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/nr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in

in g/bhp-hr	NMHC		NOx		NMHC+NOx		со		PM		HCHO	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	*	*	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	0.50	0.50	*	*	<del></del>	*	*	*	*	*
CERT	0.02	0.005	0.38	0.33	*	*	0.01	0.00	0.001	0.002	*	*
NTE	0.21		0.75		*		19.4		0.02		*	

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-24)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms. limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified. These engine models may be sold and or marketed prior to Cummins updating the engines with the revised SCR strategies approved by the Air Resources Board. Cummins shall ensure that engine models produced under this conditional Executive Order are reprogrammed in the field by December 31, 2010 to incorporate the ARB approved revised SCR strategies. The aforementioned reprogramming shall be implemented free of charge based upon a plan approved by the Air Resources Board. No later than June 30, 2010 engines models produced shall incorporate the ARB approved revised SCR strategies. Engine models produced after June 30, 2010 not incorporating the ARB approved SCR strategies will be deemed uncertified and shall be subject to penalties authorized by California laws.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

\_ day of April 2010

Annette Hebert, Chief

**Mobile Source Operations Division**