## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1608 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	YEAR ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6			
				Gasoline	PROCEDURE	CLASS T	TWC, 2HO2S, SFI, HAFS				
2011   BFMXE05.4BWI		VVL	5.4		Otto	HDO					
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL			ADDITIONAL IDLE EMISSIONS CONTROL 5								
	N/A	N/A									
ENGINE (	(L)	ENGINE MODELS / CODES (rated power, in hp)									
5.4		E450 incomplete / BE414H05 (255)									
*		*									
L=liter; hp CNG/Li L/M/H I ECS=e up catalyst TBI=throttle super char	pehorsepower; kwek NG=compressed/liqu HDD=light/medium/h mission control syste t; DPF=diesel particula le body fuel injection; ger; CAC=charge ai	ilowatt; iefied ni eavy he em; TW ilate filte SFI/Mi r cooler	hr=hour; atural gas; LPG=li pavy-duty diesel; L IC/OC≕three-way/o er; PTOX=periodic FI=sequential/mult ; EGR / EGR-C=e	quefied petroleum gas; E85=85% of JB=urban bus; HDO=heavy duty Oxidizing catalyst; NAC=NOx adsort trap oxidizer; HO2S/O2S=heated iport fuel injection, DGI=direct gas xhaust gas recirculation / cooled E	ethanol fuel; MF=mul tto; ption catalyst; SCR-t oxygen sensor; HAF oline injection; GCAF	ti fuel a.k.a. BF:  J / SCR-N=select S/AFS=heated/a RB=gaseous carl	R 86.abc=Title 40, Code of Federal Regulation  =bi fuel; DF=dual fuel; FF=flexible fuel;  stive catalytic reduction – urea / – ammonia;  pir-fuel-ratio sensor (a.k.a., universal or linear  buretor; IDI/DDI=indirect/direct diesel injection;  SPL=smoke puff limiter; ECM/PCI	WU (prefix) =warm- r oxygen sensor); on; TC/SC=turbo/			
5 ESS=e	ngine shutdown syst CR 1956.8(a)(6)(D); I	em (per E <b>xempt</b>	13 CCR 1956.8(a =exempted per 13	allel; <b>(2) (suffix)=</b> in series; )(6)(A)(1); <b>30g=</b> 30 g/hr NOx (per 1: CCR 1956.8(a)(6)(B) or for CNG/L	NG fuel systems; N/A	=not applicable	al combustion auxiliary power system; ALT= (e.g., Otto engines and vehicles);	alternative method			

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		co		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	*	0.20	*	*	*	14.4	*	0.01	*	0.01	*
FEL	*	*	*	*	*	*	*	*	*	*	*	*
CERT	0.08	*	0.14	*	*	*	4.4	*	*	*	0.001	*
NTÉ	*		*		*		*		*		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

**BE IT FURTHER RESOLVED:** Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Executed at El Monte, California on this

day of July 2010.

FOR ANDETE HEBERT

Annette Hebert, Chief

**Mobile Source Operations Division**