Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	YEAR ENGINE FAMILY		ENGINE	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6 EMD			
2011			SIZES (L)	Diesel	PROCEDURE	CLASS 2	DDI, TC, CAC, ECM, EGR, OC, PTOX, SCR, NOS				
PRIMARY	ENGINE'S IDLE		ADDITIONAL IDLE EMISSIONS CONTROL 5								
EMISSIO	ESS	N/A									
ENGINE (L) ENGINE MODELS / CODES (rated power, in hp)											
6.6		LGH / 3 (261)									
								<u> </u>			
				700 40 0 10							
	cable; GVWR≃gros =horsepower; kw=k			R xyz=1itle 13, California Code o	Regulations, Sect	ion xyz; 40 CF	R 86.abc=Title 40, Code of Federal Regulations	s, Section 86.abc;			
1 .				ied petroleum gas; E85=85% eth	anol fuel; MF=mult	i fuel a.k.a. BF	=bi fuel; DF=dual fuel; FF=flexible fuel;				
2 L/M/H H	IDD=light/medium/h	eavy heav	y-duty diesel; UB=u	rban bus; HDO=heavy duty Otto							
up catalyst; NOS=nitrog injection; T	DPF=diesel particu gen oxide sensor; TE 'C/SC≃turbo/ super	ulate filter; 31=throttle charger; (PTOX=periodic trap body fuel injection; S CAC=charge air coole	oxidizer, HO2S/O2S=heated/ox SFI/MFI=sequential/multi port fue	ygen sensor; HAF injection; DGI=dir ecirculation / cooled	S/AFS=heated/ ect gasoline inje EGR; PAIR/A	ctive catalytic reduction – urea / – ammonia; W air-fuel-ratio sensor (a.k.a., universal or linear o cction; GCARB=gaseous carburetor; IDI/DDI= IR=pulsed/secondary air injection; SPL=smoke	xygen sensor); indirect/direct diese			
ESS=er (per 13 CCI	ngine shutdown syst R 1956.8(a)(6)(D);	em (per 1: E xempt =e	3 CCR 1956.8(a)(6)(exempted per 13 CCF	A)(1); 30g= 30 g/hr NOx (per 13 0 R 1956.8(a)(6)(B) or for CNG/LNG	CR 1956.8(a)(6)(C fuel systems; N/A); APS =intern =not applicable	al combustion auxiliary power system; ALT=all e(e.g., Otto engines and vehicles);	ernative method			
EMD=e	engine manufacturer	diagnosti	c system (13 CCR 19	971); OBD=on-board diagnostic s	ystem (13 CCR 19	71.1);					

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		со		PM		нсно	
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	•	· -	•	*.	15.5	15.5	0.01	0.01	0.050	0.050
FEL	*	•	0.46	0.46	•	•	*	•	•	•		*
CERT	0.01	0.000	0.32	0.21	•	•	0.3	0.00	0.000	0.000	0.003	0.000
NTE	0.21		0,69		•		19.4		0.02		0.075	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes and cancels Executive Order A-006-1738 dated May 20, 2010.

Executed at El Monte, California on this / / day of July 2010.

Annette Hebert, Chief

Mobile Source Operations Division