

EO back

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-112
Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Ford Motor Company exhaust emission control systems for 1978 model-year light duty trucks are certified for the vehicles described below:

- Engine Family: 351W "A" (1X100)
- Engine: 351 - CID
- Transmission: 3-speed Automatic
- Exhaust Emission Control Systems: Air Injection, Exhaust Gas Recirculation, Oxidation Catalyst

Models and Engine Codes as listed in attachment.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1978 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
351W "A" (1X100)	0.7	6	1.7


BE IT FURTHER RESOLVED: That the above models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (13 California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-10 series.

BE IT FURTHER RESOLVED: That the above models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-powered Motor Vehicles except Motorcycles".

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 17 day of August, 1977.



G. C. Hass, Chief
Vehicle Emissions Control Division

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Ford Motor Company Executive Order No. A-10-112 Page 1

Engine Family 351W "A" (1X100) Engine (CID) 351

ABBREVIATIONS

Distributor

C-Centrifugal Advance
V-Vacuum Advance
VR-Vacuum Retard
HEI-High Energy Ignition
EI-Electronic Ignition

Fuel System

EFI, FI
nV-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection
CAI-Catalyst Air Injection
CAB-Chamber Air Bleed
DD-Dual Displacement
EFI-Electronic Fuel Injection
EGR-Exhaust Gas Recirculation
EM-Engine Modification
EFE-Early Fuel Evaporation
ESAC-Electronic Spark Advance Control
FI-Fuel Injection

OC-Oxidation Catalyst
PAI-Pulse Air Injection
RC-Reduction Catalyst
TC-Turbo Charged
TR-Thermal Reactor
TWC-Three Way Catalyst
(Feedback Control)
EGR Syst. Service
I-Inspect, repair/replace
As needed
R-Replace

<u>Model</u>	<u>Body Type</u>	<u>Wheelbase</u>	<u>Box Design</u>	<u>Trim Levels</u>
E-100	Regular Van Club Wagon	SWB or LWB SWB	A,B, or C -	1,2,3 1,2,3,

<u>Wheelbase</u>	<u>Box Design</u>	<u>Trim Level</u>
SWB Short Wheelbase	A. Cargo Van	1. Standard
LWB Long Wheelbase	B. Display Van	2. Custom
	C. Window Van	3. Custom

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars Light-Duty Trucks Medium Duty Vehicles

Manufacturer Ford Motor Company Executive Order No. A-10-112 Page 2

Engine Family 351 W "A" (1 X 100) Engine (CID) 351 Engine Code 8-65U-RO

Emission Control System EGR, AI, OC +10%(A/C) Yes No

Eng. Code	Vehicle Models (If Coded see attachment)	Trans	Inertia Weight Class RLHP	Distributor Type c, v Mfgr. Part Number	Fuel System Type 2 v Mfgr. Part Number	EGR System Part No. Service**	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
	E-100 Van SWB, LWB Club Wagon SWB	A-3	<u>4500</u> <u>19.0</u>	Ford D7UE-12127-AA	Ford D8UE-9510-HA	D8UE-9D448-GA	(1) 10° BTDC \pm 2° @ 500 RPM in neutral w/ vacuum line disconnected and plugged at distributor (2) Preset at factory. Do not adjust. See Ford 1978 Service Manual. (3) 700 ± 50 RPM in drive. 500 ± 50 RPM in neutral with TSP Off. All hoses connected.

Comments: All models have special road load HP settings.
See page 1 for abbreviations and model codes.
** No service required

Date of Issue 081877 Revisions: