State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-134-1 Relating to Certification of New Motor Vehicles

MUSKETEER MFG. CO.

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Musketeer Mfg. Co. exhaust emission control systems for 1978 model-year light-duty trucks are certified for the vehicles described below:

Engine Family: 20R (TC)
Displacement: 133.6 CID

Exhaust Emission Control Systems: Air Injection, Exhaust Gas

Recirculation, Oxidation Catalyst

Models, Transmissions and Engine Codes as listed in attachment.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1978 model-year vehicles:

Engine Family	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
	Grams per Mile	Grams per Mile	Grams per Mile
20R (TC)	0.2	9	1.7

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (13 California Administrative Code, Section 2290) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-powered Motor Vehicles except Motorcycles".

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this _____ day of April, 1978.

G. C. Hass, Chief

Vehicle Emissions Control Division

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Musketeer Mfg.	Co. Executive Order No. A-134	<u>-1 Page 1 </u>
Engine Family 20R (TC)	Engine (CID) <u>133.6</u>	
ABBREVIATIONS Distributor C-Centrifugal Advance V-Vacuum Advance VR-Vacuum Retard HEI-High Energy Ignition EI-Electronic Ignition Fuel System EFI, FI nV-nVenturi Carburetor VV-Variable Venturi	Exhaust Emissions Control Syst AI-Air Injection CAI-Catalyst Air Injection CAB-Chamber Air Bleed DD-Dual Displacement EFI-Electronic Fuel Injection EGR-Exhaust Gas Recirculation EM-Engine Modification EFE-Early Fuel Evaporation ESAC-Electronic Spark Advance Control FI-Fuel Injection	OC-Oxidation Catalyst PAI-Pulse Air Injection RC-Reduction Catalyst TC-Turbo Charged TR-Thermal Reactor TWC-Three Way Catalyst (Feedback Control) EGR Syst. Service I-Inspect, repair/replace as needed R-Replace
Engine Code	Model Tra	nsmission

Muskeet Mini Motorhome

4M

CM-CT

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

		□ Passen	ger Can	rs D	☑ Light-Duty	Trucks	Medium Dut	y Vehicles
	Manu	facturer Muske	t Mfg.	Co.	Execu	ti ve Order No	o. <u>A-134-1</u>	Page2
	Engi	ne Family 20R	(TC)	(Toyota)	Engin	e (CID) 133.	.6	Engine Code
	Emis:	sion Control Sy	stem _	AI, E	GR, OC		+10%(A/C)	Yes 🗆 No 첩
		Vehicle Models (If Coded see attachment)		Weight Class	Type Mfgr.	Fuel System Type Mfgr. Part Number	Part No.	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
	CM-CT	Muskeet Mini Motorhome	4M	4000	19100-38060	21100-38161	25620- 38121	(1) 8° BTDC @ Idle. (2) Lean drop idle. (3) 800 RPM. Lean Drop Method Set to the following value at best idle . 870M, 920A, RPM turn idle mixture adjusting screw until 800M, 850A.
Comments: models have special road load HP settings. See page 1 for abbreviations and model codes. (41.1 Sq. Ft. x 0.58 = 24 H.P.)								s = 24 H.P.)
Date of Issue Revisions: April 1, 1978								