

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-116-2  
Relating to Certification of New Motor Vehicles

SPECIALIZED AUTOMOTIVE ENGINEERING, INC.

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Specialized Automotive Engineering, Inc. exhaust emission control systems for 1978 model-year light-duty trucks are certified for the vehicles described below:

Engine Family: 2OR (TC)  
Engine: 133.6  
Transmission: 4-speed manual, 5-speed manual  
Exhaust Emission Control Systems: Air Injection, Exhaust Gas Recirculation, Oxidation Catalyst

Models and Engine Codes as listed in attachment.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1978 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
2OR (TC)	0.3	6	1.8


BE IT FURTHER RESOLVED: That the above models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (13 California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-14-1 series.

BE IT FURTHER RESOLVED: That the above models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-powered Motor Vehicles except Motorcycles".

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 22 day of December, 1977.



G. C. Mass, Chief  
Vehicle Emissions Control Division

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Specialized Automotive  
 Manufacturer Engineering, Inc. Executive Order No. A-116-2 Page 1  
 Engine Family 20R (TC) Engine (CID) 133.6

ABBREVIATIONS

Distributor

C-Centrifugal Advance  
 V-Vacuum Advance  
 VR-Vacuum Retard  
 HEI-High Energy Ignition  
 EI-Electronic Ignition  
Fuel System  
 EFI, FI  
 nV-nVenturi Carburetor  
 VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection  
 CAI-Catalyst Air Injection  
 CAB-Chamber Air Bleed  
 DD-Dual Displacement  
 EFI-Electronic Fuel Injection  
 EGR-Exhaust Gas Recirculation  
 EM-Engine Modification  
 EFE-Early Fuel Evaporation  
 ESAC-Electronic Spark Advance  
 Control  
 FI-Fuel Injection

OC-Oxidation Catalyst  
 PAI-Pulse Air Injection  
 RC-Reduction Catalyst  
 TC-Turbo Charged  
 TR-Thermal Reactor  
 TWC-Three Way Catalyst  
 (Feedback Control)  
EGR Syst. Service  
 I-Inspect, repair/replace  
 as needed  
 R-Replace

ENGINE CODE

MODEL

TRANSMISSION

CM-PT	Wolverine 4 x 4 Light-Duty Truck #1	4M
	Wolverine 4 x 4 Light-Duty Truck #2	4M
	Wolverine 4 x 4 Light-Duty Truck #1	5M
	Wolverine 4 x 4 Light-Duty Truck #2	5M
CM-CT	Wolverine 4 x 4 Light-Duty Truck Cab & Chassis	4M

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars     Light-Duty Trucks     Medium Duty Vehicles

Manufacturer Specialized Automotive Engineering, Inc.    Executive Order No. A-116-2    Page 2

Engine Family 20R (TC)    Engine (CID) 133.6    Engine Code \_\_\_\_\_

Emission Control System AI, EGR, OC    +10%(A/C)    Yes     No

Eng. Code	Vehicle Models (If Coded see attachment)	Trans	Inertia Weight Class	Distributor Type G, V Mfgr. Part Number	Fuel System Type 2V Mfgr. Part Number	EGR System Part No. Service	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
CM-PT	Hilux Pickup Truck No. 1, 2	4M 5M	2750 3000	19100-38060	21100-38161	25620-38121	1) 8° BTDC @ Idle 2) Lean drop idle 3) 800 RPM
CM-CT	Cab & Chassis	4M	3500		21100-38151		<u>Lean drop method</u>  Set to the following value at best idle 870M RPM turn idle mixture adjusting screw until 800M.

Comments: No models have special road load HP settings. See page 1 for abbreviations and model codes.

Date of Issue 122177    Revisions: