

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-6-141
Relating to Certification of New Motor Vehicles

GENERAL MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That General Motors Corporation exhaust emission control systems are certified as described below for 1979 model-year gasoline-powered passenger cars:

<u>Engine Family</u>	<u>Displacement Cubic Inches</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
960J0	350	Air Injection Exhaust Gas Recirculation Oxidation Catalyst (Electronic Fuel Injection) (Electronic Spark Advance Control)

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1979 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
960J0	0.29	4.6	1.3

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year.


GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-6-141
(Page 2 of 2)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 16 day of August, 1978.



G. C. Hass, Chief
Vehicle Emissions Control Division

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer General Motors Corp. Executive Order No. A-6-141 Page 1

Engine Family 960J0 Engine (CID) 350

Evap Family 9B0-6

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance
 EI-Electronic Ignition
 ESAC
 VA-Vacuum Advance
 VR-Vacuum Retard

Fuel System

EFI, MFI
 nV-nVenturi Carburetor
 VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection
 CCAV-Comb. Chamber Air Valve
 EFI-Electronic Fuel Injection
 EGR-Exhaust Gas Recirculation
 EM-Engine Modification

ESAC-Electronic Spark Advance Control
 MFI-Mechanical Fuel Injection

OC-Oxidation Catalyst
 PAI-Pulse Air Injection
 TC-Turbo Charged
 TR-Thermal Reactor
 TWC-Three Way Catalyst
 (Feedback Control)
 WOC-Warm-up Oxidation Catalyst

Division	Basic Body	Trim	Body Type
6			<u>Cadillac</u>
	E	L	57 Eldorado

AIR RESOURCES BOARD 1979 SUPPLEMENTAL DATA SHEET - GM FORMAT
Passenger Cars

Manufacturer: GENERAL MOTORS CORPORATION Executive Order No. A-6-141

Engine Family 960J0 Engine CID 350 Transm. Auto-3

Exhaust Emission Control System AI /EGR/OC +10% (A/C) Yes No

Eng. Code	Air Cond.	Ign.Syst. EI,CA,VA ESAC Distrib. Part No.	Fuel System EFI ECU Part No.	EGR Valve Part No.	Inertia Wt. Class	Divisions	Basic Body	Trim	Body Type	Trans- mission	Tune-up Label & Page No.	Rev. Notes
1 1a	W	Delco Remy 1103307	Bendix 1615139	17053046	4000	6	E	L	57	A-3	MS 3	A
1b											MW 3	B
1c												C
1d												D
1e											MS	E

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP lists for correct dyno test HP settings based on model, equipment and inertia weight class.

Date of Issue: 081778 **Revisions:** A. EC 1a added by RC 96-37, on 100478. B. EC 1b added by RC 96-93, on 103178. C. EC 1c added by RC 96-159, on 031379. D. EC 1d added by RC 96-162, on 032179. E. EC 1e added by RC 96-164, on 052379.

MS * 960JD 980-6 5.7 LITRE	VEHICLE EMISSION CONTROL INFORMATION GENERAL MOTORS CORPORATION	CATALYST AIR: E.G.R. LOW ALTITUDE CERTIFICATION <table border="1"> <tr> <td>TIMING (DEG. B.I.D.C. @ R.P.M.)</td> <td>D @ 600</td> </tr> <tr> <td>SPARK PLUG GAP (INCHES)</td> <td>0.00</td> </tr> <tr> <td>THROTTLE BODY SCREW (R.P.M.)</td> <td>600</td> </tr> </table>	TIMING (DEG. B.I.D.C. @ R.P.M.)	D @ 600	SPARK PLUG GAP (INCHES)	0.00	THROTTLE BODY SCREW (R.P.M.)	600
	TIMING (DEG. B.I.D.C. @ R.P.M.)		D @ 600					
SPARK PLUG GAP (INCHES)	0.00							
THROTTLE BODY SCREW (R.P.M.)	600							
1. PLACE TRANSMISSION IN PARK AND BLOCK DRIVE WHEELS 2. DISCONNECT AND PLUG VACUUM LINE TO PARKING BRAKE RELEASE TO PREVENT AUTOMATIC RELEASE OF PARKING BRAKE WHEN SHIFTING TRANSMISSION IN STEP 7. 3. SET PARKING BRAKE 4. WITH ENGINE AT NORMAL OPERATING TEMPERATURE, AIR CLEANER OFF AND AIR CONDITIONER OFF, MAKE ENGINE ADJUSTMENTS AS FOLLOWS: 5. DISCONNECT AND PLUG DISTRIBUTOR VACUUM LINE 6. WITH TRANSMISSION IN "PARK" SET TIMING AT SPECIFIED R.P.M. 7. RECONNECT DISTRIBUTOR VACUUM LINE PLACE TRANSMISSION IN "DRIVE" AND ADJUST THROTTLE BODY SCREW TO SPECIFIED R.P.M. 8. RECONNECT PARKING BRAKE RELEASE LINE SEE SERVICE MANUAL AND MAINTENANCE SCHEDULE I FOR ADDITIONAL INFORMATION THIS VEHICLE CONFORMS TO U.S. EPA AND CALIFORNIA REGULATIONS APPLICABLE TO 1979 MODEL YEAR NEW PASSENGER CARS	ELECTRONIC FUEL INJECTION NO ADJUSTMENT PROVISIONS EXIST FOR IDLE FUEL MIXTURE							

Eng. Fam. 960 JD PART NO. 1616871

MW * 960JD 980-6 5.7 LITRE	VEHICLE EMISSION CONTROL INFORMATION GENERAL MOTORS CORPORATION	CATALYST AIR: E.G.R. LOW ALTITUDE CERTIFICATION <table border="1"> <tr> <td>TIMING (DEG. B.I.D.C. @ R.P.M.)</td> <td>B @ 600</td> </tr> <tr> <td>SPARK PLUG GAP (INCHES)</td> <td>0.00</td> </tr> <tr> <td>THROTTLE BODY SCREW (R.P.M.)</td> <td>600</td> </tr> </table>	TIMING (DEG. B.I.D.C. @ R.P.M.)	B @ 600	SPARK PLUG GAP (INCHES)	0.00	THROTTLE BODY SCREW (R.P.M.)	600
	TIMING (DEG. B.I.D.C. @ R.P.M.)		B @ 600					
SPARK PLUG GAP (INCHES)	0.00							
THROTTLE BODY SCREW (R.P.M.)	600							
1. PLACE TRANSMISSION IN PARK AND BLOCK DRIVE WHEELS 2. DISCONNECT AND PLUG VACUUM LINE TO PARKING BRAKE RELEASE TO PREVENT AUTOMATIC RELEASE OF PARKING BRAKE WHEN SHIFTING TRANSMISSION IN STEP 7. 3. SET PARKING BRAKE 4. WITH ENGINE AT NORMAL OPERATING TEMPERATURE, AIR CLEANER OFF AND AIR CONDITIONER OFF, MAKE ENGINE ADJUSTMENTS AS FOLLOWS: 5. DISCONNECT AND PLUG DISTRIBUTOR VACUUM LINE 6. WITH TRANSMISSION IN "PARK" SET TIMING AT SPECIFIED R.P.M. 7. RECONNECT DISTRIBUTOR VACUUM LINE PLACE TRANSMISSION IN "DRIVE" AND ADJUST THROTTLE BODY SCREW TO SPECIFIED R.P.M. 8. RECONNECT PARKING BRAKE RELEASE LINE SEE SERVICE MANUAL AND MAINTENANCE SCHEDULE I FOR ADDITIONAL INFORMATION THIS VEHICLE CONFORMS TO U.S. EPA AND CALIFORNIA REGULATIONS APPLICABLE TO 1979 MODEL YEAR NEW PASSENGER CARS	ELECTRONIC FUEL INJECTION NO ADJUSTMENT PROVISIONS EXIST FOR IDLE FUEL MIXTURE							

E.O. A-6-141 S.D. Sheet 3