State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-255 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1984 model-year Ford Motor Company exhaust emission control systems are certified as described below for diesel-powered passenger cars:

Engine Family	Displacement Cubic Inches (Liters)		Exhaust Emission Control Systems (Special Features)		
		(2.4)	Exhaust Gas Recirculation (Diesel Injection - Prechamber) (Turbocharger)		

Vehicle models, transmissions and engine codes are listed on attachments.

The following are the emission standards for this engine family to be listed on the window decal required by "California Assembly-Line Test Procedures for 1983 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles".

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
Grams per Mile	Grams per Mile	Grams per Mile
0.46	8.3	1.0

The following are the certification emission values for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	
Grams per Mile	Grams per Mile	Grams per Mile	
0.14	1.4	0.8	

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

day of December, 1983.

K. D. Drachand, Chief Mobile Source Division Hanufacturer Ford Motor Company Executive Order No. A-10-255

Engine Family EFM2.4D6JAC2 Evaporative Family Not App.

Engine CID (Liters) 149 (2.4)

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance EEC-Electronic Engine Control EI-Electronic Ignition ESAC-Electronic Spark Advance Control VA-Yacuum Advance VR-Yacuum Retard

Fuel System
CFI, CL, DID, DIP, EFI, MFI
V-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emissions Control System

AIP-Air Injection-Pump AIV-Air Injection-Valve CL-Closed Loop EGR-Exhaust Gas Recirculation EM-Engine Modification OC-Oxidation Catalyst System TR-Thermal Reactor TWC-Three-Way Catalyst System

Special Feature

CCY-Combustion Chamber Va CFI-Central Fue Injection DID-Diesel Injection-Direct DIP-Diesel Injection-Prechamber EFI-Electronic Fue 1 Injection FI-Mechanical Fue 1 Injection

TC-Turbocharged

VEHICLE MODELS:

Vehicle Line	Body Type (Cab Style)	Body Code (Wheelbase)
Mark VII	2 Dr Sedan	63D
Continental	4 Dr Sedan	54D

DRIVE SYSTEM: Front Engine/ Rear -Wheel Drive

E.O. 1A-10-255

198 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Ford Motor Company Engine Family EFM2.4D6JAC2 ECS (Special Features) MFI,DIP,EGR,Controlled Start of Injection				Page 2 Engine Code 4-40S-R00A CID (Liter)- Type 149 (2.4)-L6			
Engine Code	Vehicle Models (If Coded see attachment) (Non-A/C Dyno Hp)	Trans.	Equiv. Test Weight	Ign. System Part No.	Fuel System Injection Pump Part No.	EGR Valve	Label Ident. Part No
4-40s-R00A	Mark VII 63D (8.3) Continental 54D (10.0)	A4-OD	4000 4000	Not App.	1.287 433	1.285 112	E4AE- 9C485- AYM
•			•				·
		•					
		·					

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

*Add 10% to dyno test HP for air conditioning usage.

Date of Issue -