

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-15-80  
Relating to Certification of New Motor Vehicles

NISSAN MOTOR COMPANY, LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1985 model-year Nissan Motor Company, Ltd. exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

<u>Engine Family</u>	<u>Displacement Cubic Inches (Liters)</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
FNS2.OV5FAC0	120.4 (2.0)	Exhaust Gas Recirculation Three-Way Catalyst with Closed Loop (Electronic Fuel Injection)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the certification emission standards for this engine family to be listed on the window decal required by "California Assembly-Line Test Procedures for 1983 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles":

<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
0.39	7.0	0.7

The following are the certification emission values for the above engine family:

<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
0.22	2.7	0.4

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.15 of Title 13, California Administrative Code which includes repair or replacement of emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 10<sup>th</sup> day of August, 1984.



K. D. Drachand, Chief  
Mobile Source Division

## 17.01.03.00 Test Weight/Horsepower List

Vehicle Model	Test Weight	Test Horsepower		
		Determination Method	With A/C factor	Without A/C factor
4-DOOR SEDAN GL	2,625	Coastdown	8.7	7.9
4-DOOR SEDAN XE				—
	2,750			

Issue Date: 05/24/84

Revision Date:

7.01.02.00

## 1985 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer NISSAN MOTOR CO., LTD. Executive Order No. A-15-80  
 Engine Family FNS2.0V5FACO Evaporative Family 5FI4-2  
 Engine CID (Liters) 120.4C.I.D. (2.0 l)

## ABBREVIATIONS

Ignition System

CA-Centrifugal Advance  
 EEC-Electronic Engine Control  
 EI-Electronic Ignition  
 ESAC-Electronic Spark Advance Control  
 VA-Vacuum Advance  
 VR-Vacuum Retard

Fuel System

CFI, CL, DID, DIP, EFI, MFI  
 nV-nVenturi Carburetor  
 V-Variable Venturi

Exhaust Emissions Control System

AIP-Air Injection-Pump  
 AIV-Air Injection-Valve  
 CL-Closed Loop  
 EGR-Exhaust Gas Recirculation  
 EM-Engine Modification  
 OC-Oxidation Catalyst System  
 TR-Thermal Reactor  
 TWC-Three Way Catalyst System  
 ECC-Electronic Control Carburetor  
 ECCS-Electronic Concentrated Control System

Special Features

CCV-Combustion Chamber Valve  
 CFI-Central Fuel Injection  
 DID-Diesel Injection-Direct  
 DIP-Diesel Injection-Prechamber  
 EFI-Electronic Fuel Injection  
 MFI-Mechanical Fuel Injection  
 TC-Turbocharged

VEHICLE MODELS:

STANZA	AC20ECM2 BC20ECM2 AC20ECA2 BC20ECA2	} STANZA 4-DOOR SEDAN GL STANZA 4-DOOR SEDAN XE	{ 5-speed Manual Automatic
--------	--	--	-------------------------------

DRIVE SYSTEM: Front Engine/ Front -Wheel Drive

Issue Date: 05/24/84

Revision Date:

17.01.02.00 - cont.

E.O. #A-15-80

AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars  Light-Duty Trucks  Medium-Duty Vehicles  Gas  Diesel

Manufacturer NISSAN MOTOR CO., LTD. Page \_\_\_\_\_  
 Engine Family FNS2.OV5FACO Engine AC20ECM2, AC20ECA2  
 CID (Liter)<sup>9</sup>- 120.4 CID (2.0 liter) Code BC20ECM2, BC20ECA2  
 ECS (Special Features) EFI/EGR/TWC/CL/2plug Type - L4

Engine Code	Vehicle Models (If Coded see attachment)	Trans.	Equiv. Test Weight	Ign. System Part No.	Fuel System Part No.	EGR Valve Part No.	Label Ident. Part No.
AC20ECM2 BC20ECM2	STANZA 2DOOR SEDAN GL	M-5	26 25	Distributor D4N84-08 (HITACHI) TOT60273 (MISTUBISHI)	Control Unit All-668 Air Flow Meter A31-632 Injector A46-001 (JECS) A46-002 (DKC)	AEY76-85	Vehicle Emission Control Information 14805 D3405
AC20ECA2 AC20ECA2	STANZA 2DOOR SEDAN XE	L-3	26 25 2750	Distributor D4N83-16 (HITACHI) TOT60274 (MISTUBISHI)	Control Unit All-669 Air Flow Meter A31-632 Injector A46-001 (JECS) A46-002 (DKC)	AEY76-84	Vacuum Hose Routing Diagram 22304 D3300

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment on 17.01.03.00. If two test weights are listed, the lower weight will be used for testing.

\*Add 10% to dyno test HP for air conditioning usage.

Issue Date: 05/24/84  
 Revision Date: