

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-254-42
Relating to Certification of New Motor Vehicles

HYUNDAI MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Hyundai Motor Company exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: THY3.0V8G1FK Displacement: 3.0 Liters (181.4 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Exhaust Gas Recirculation
- Heated Oxygen Sensors (two)
- Three Way Catalytic Converter
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.15	0.5	0.2	6.9
100,000	0.15	0.5	0.2	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

HYUNDAI MOTOR COMPANY

EXECUTIVE ORDER A-254-42
(Page 3 of 3)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 15th day of November 1995.



R. B. Summerfield
Assistant Division Chief
Mobile Source Division

1996 AIR RESOURCES SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer : HYUNDAI MOTOR CO. Exh Eng Fam : THY3.0V8G1FK Evap Fam : THY1039BYM07
 All Eng Codes in Eng Fam : CA X 49S ___ 50S ___ AB965 ___
 Exh Std : CA Tier-1 X TLEV___ LEV___ ULEV___ ZEV___ ; US EPA Tier-1 ___
 Evap Std : 50K X Useful life with R/L___ In-Use Exh Std : Full In Use X Alt In Use ___
 Veh Class(es) : PC X LDT1___ LDT2___ MDV1___ MDV2___ MDV3___ MDV4___ MDV5___
 Single Cert Std for Multi-Class Eng Fam : N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
 Fuel Type(s) : Dedicated___ Flex-Fuel___ Dual-Fuel___ Bi-Fuel___ Gasoline X Diesel___
 CNG ___ LNG ___ LPG ___ M85 ___ Other (specify) ___
 Emiss Test Fuel(s) : Indo X PH2___ CNG___ LPG___ M85___ other(specify) ___
 Diesel : 13 CCR 2282___ 40 CFR 86.113-90___ 40 CFR 86.113-90___
 Service Accum : Std AMA X Modl AMA ___ Mfr ADV___ OTHER (SPECIFY) ___
 NMOG Test procedure : N/A X Std___ Equiv___ R/L Test Proc : SHED___ Pt Source___
 Hybrid : Type A___ B___ C___, APU Cycle (e.g., Otto, Diesel, Turbine) ___
 Engine Configuration : V-6 Displacement : 3.0 / ___ Liters 181.4 / ___ Cubic Inches
 Valves Per Cylinder : 2/6 Rated HP : 142 @ 5000 RPM
 Engine : Front X Mid___ Rear___ Drive : FWD X RWD___ 4WD-FT___ 4WD-PT___
 Exhaust ECS (e.g., MFI EGR,, TC, CAC) : HO2S(2) + EGR + TWC + SFI +
 (use abbreviations per SAE J1930 SEP91)

Eng. Code (list CA/ 49ST/50ST)	Veh. Models (If Coded see Attachment)	Trans. Type : L-Auto. M-Man.	Equiv. Test Weight	DPA or RLHP	Ign. Sys. (ECM/TCM) part No.	EGR System. Part No.	Catalyst Part No.
ACL4-T /CL4-T	SONATA	L4	3375	7.8	39110-351100 (CAVM2) or 39110-35160 (CAVM2)	28480-35080 (TF) 28480-35090 (JTF)	28950-35120

Issued : 11-1-95
Revised :