Fale

(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-211 Relating to Certification of New Motor Vehicles

MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Mazda Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TTK2.5VJGFEK <u>Displacement</u>: 2.5 Liters (152 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Warm Up Three-Way Catalytic Converters Three Way Catalytic Converter Dual Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (in-use compliance standards in parentheses) for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>
50,000	0.25 (0.32)	3.4 (5.2)	0.4 (0.4)	10.0 (10.0)
100,000	0.31 (n/a)	4.2 (n/a)	0.6 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	Monoxide (20°F)
50,000	0.16	1.4	0.1	6.8
100,000	0.18	1.6	0.1	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 20 percent of the manufacturer's projected sales of 1996 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 16 day of August 1995.

R. B. Summerfield

Assistant Division Chief Mobile Source Division

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

E.O.# A-16-211 page 2 of 2

	Mazda Motor Corpor	etion.	Engine Fa	mily		C2,5VJGFEK	
Manufacturer _	Mazda Motor Corpor	auon	Evap Fam		TTI	C1078BYPA1	
_	04	408	FAC V				
All Eng Codes in	Eng Fam: CA_ rier-1 <u>X</u> AB96	493	_000 <u>_7-</u>	- ULE	v ZEV_	US EPA	A Tier 1 X
Stds. Type: CA	Tier-1 <u>X</u> AB96	ILEV_	In-Lise	Exh Std:	Multi-Class En	Alt In	Use X
Evap Std:	50K PC		Single	Cert Std for	Multi-Class En	g Fam: N/A	
Veh. Calss:	PC		Emicei	on Test Fu	el(s):	Indoler	e
Fuel Type(s):	Gasoline		Cition	011 10011 0			
Service Accum:	Std AMA		D# Te	ot Drocedi	ıre:	N/A	
NMOG Test Prod	cedure: N/A		*			-Gitto-	
Hybrid:	N/A		APUC	Cycle:	2.5 Liters	(152.4)	Cu. inches
Engine Config :	V-6		Displa	cement .		5800 RF	-
Valves/Cly.	4		Rated	HP	170 @ RWD		 IWD-PT
Engine : Front	X Mid.	Rear	Drive:	FWD X	KWD '	+VVD-F1	
					(z) Z		
Fuhaust ECS &	Special Feature (inc	L CARB, MFI,	etc.)	2	HO2\$/SFI/WU-1	WC/TWC/EGE	
Exhaust Eco a	tions per SAE J193	0 MAY91)	· -				
(Use apprevia				DPA	Ignition	EGR	i
	Vehicle Model	Trans. Type	ETW	or	(ECM/PCM)	System	Catalyst
Engine Code	(if coded see	A-autonatic	□ □ 1 AA	RLHP	Part No.	Part No.	Part No.
(Cert, Std.)	attachment)	M-manual			<u> </u>	EGR	Monolith
FKLDTAAT	Millenia	A4	3625	5.8	Distributor:	ŀ	Converter:
					KF34	Control	ł
						Valve:	KLG9
] 			KLG8	KL50
				<u> </u>	ECU:		KL50
				ļ	KLG8	}	
	·				REG8		
		l			1		
ļ			1				1
ļ		1					
		1				}	
•					į	-	
			1	1		Ĭ	
1		1	1		1	1	1
		1		1	<u> </u>		1
		1					1
{						1	
ł				<u> </u>			
Povisions:							

Revisions: 1290

Issue date:	June 30, 1995	
Rev. No.		
Date		<u> </u>