State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-158-A Relating to Certification of New Motor Vehicles

MERCEDES-BENZ AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Mercedes-Benz AG exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TMB6.0VJGFEK Displacement: 6.0 Liters (365 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Secondary Air Injection
Dual Three Way Catalytic Converters
Dual Heated Oxygen Sensors (Two)
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (in-use compliance standards in parentheses) for this engine family in grams per mile are:

	Non-Methane	Carbon	Nitrogen	Carbon
<u>Miles</u>	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	Monoxide (20 ⁰ F)
50,000	0.25 (0.32)	3.4 (5.2)	0.4 (0.4)	10.0 (10.0)
100,000	0.31 (n/a)	4.2 (n/a)	0.6 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane <u>Hydrocarbons</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	Carbon <u>Monoxide (20⁰F)</u>	
50,000	0.14	1.2	0.1	3.3	
100,000	0.14	1.3	0.1	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 20 percent of the manufacturer's projected sales of 1996 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label—Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 25 day of September 1995.

R. B. Summerfield

Assistant Division Chief Mobile Source Division

199<u>6</u> MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Page_/_

Manufacture	r: Mercedes-Benz		Exh Eng F	am: TMB	6.0VJGFEK	Evap Fam: TMB	1030AYMA0
All Eng Code	es in Eng Fam: C	A	4 9S	50S_2	<u>x</u> - AB965	_	
Exh Std: CA	A Tier-1 <u>X</u> T	LEV	LEV	ULE	V ZEV	; US EF	PA Tier-1 X
Evap Std: 5	OK <u>X</u> Useful L	ife with 1	R/L	In-Use	Exh Std: Full	In Use	Alt In Use X
Veh Class(es	s): PC <u>X</u> LDT1	LDT:	2Y	/1	MDV2 MDV	3 MDV4	MDV5
Single Cert	Std for Multi-Cla	ass Eng Fa	am: N/A	(speci	fy: N/A, LDT1	, MDV1, MDV2.	MDV3. MDV4)
Fuel Type(s)	: DedicatedX	Flex-Fuel	Dual	-Fuel_	Bi-Fuel	Gasoline X	Diesel
	CNG LNG	_ LPG	M85	Other -	(specify)		
Emiss Test F	uel(s): Indo X	Ph2	CNG	.PG	M85Othe	r (specify)	
	Diesel:	13 CCR 2	282	40 (CFR 86.113-90_	40 CFR	86.113-94
Service Accu	m: Std AMA <u>X</u>	Mod AMA	Mfr	ADP	Other (spec	 ify)	-
NMOG Test Pr	ocedure: N/A <u>X</u>	Std	_ Equiv_		R/L Test Proc	: SHED	Pt Source
Hybrid: Typ	e A B C,	APU Cyc	le (e.g.,	Otto,	Diesel, Turbia	ne):	
Engine Confi	guration: <u>v-12</u>	Displace	ment: <u>6.</u>	0 /	Liters	365 /	Cubic Inches
Valves per C	ylinder: <u>4</u>		Rate	d HP:	389	@ 5200	RPM
F၈ဥ္ he: Fro	nt <u>X</u> Mid	Rear	Driv	e: FWD	RWD_X	4WD-FT	4WD-PT
.haust ECS	(e.g., MFI, EGR,	TC, CAC):	SFI/AIR	/2HO2S(2)2TWC/OBDII		
	•		(u	se abbr	eviations per	SAE J1930 SE	P91)
Engine Code	Vehicle Models	Trans.	ETW	DPA	Ignition	EGR	Catalytic
(also list CA/49ST/50ST	(if coded see attachment)	(M5, A4 etc.)	Or Tast Wt	or	(ECM/PCM) Part No.	System	Converter
			TESU HU.	NCTIP-	Part No.	Part No.	Part No.
M120-3	SL600	A5	4750	6.6	0205452232		129 490 48 14
							129 490 47 14
							129 490 21 14
							129 490 20 14
İ							
			į				
	ļ						
		Ì			!		
			ĺ				
		}			·		
ate Issued:			·				