State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-297 Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TTY3.0VJGKHK Displacement: 3.0 Liters (182.9 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Exhaust Gas Recirculation Heated Oxygen Sensors (two) Three Way Catalytic Converters (two) Turbochargers (two) Charge Air Cooler

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane <u>Hydrocarbons</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	Monoxide (20 ⁰ F)	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>
50,000	0.16	0.9	0.2	9.7
100,000	0.16	1.3	0.2	n/a

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this $\frac{2!}{2!}$ day of December 1995.

R. B. Summerfield

Assistant Division Chief Mobile Source Division

hu Konsloli for

E.O.# A - 14 - 297
Page 1401

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

	•	
Manufacturer: TOYOTA All Eng Codes in Eng Fain: CA Exh Std. CA Times	Exh Eng Fam: TTY3.0VJGKHK 49S 50S x AB965	Evap Fam: TTY1095BYPA0
Exh Std: CA Tier-1 x TLEV Evap std: 50K x Useful Life with Class(es): PC x LDT1	LEV <u>ULEV</u> 7.1 ith R/L In-Use Exh Std:	Full In Use x Alt In Use
Single Cert Std for Multi-Class Eng Fa	m: N/A (specify: N/A,	MDV3 MDV4 MDV5 LDT1, MDV1, MDV2, MDV3, MDV4)
Emiss Test Fuel(s): Indo x Ph2	LPG M85 Ot.	Fuel Gasoline x Diesel her(specify)
Diesel: 13CC Service Accum: Std AMA x Mi	CR 2282 40 CFR 86.113-90	Other(specify) 40 CFR 86.113-94 ner(specify)
Hybrid: Type A B Sto		Proc: SHED Dt Saves
valves per Cylinder: 4	Rated HP: 320	Liters 182.9 / Cubic Inches
Engine: Front x Mid Rear Exhaust ECS(e.g., MFI, EGR, TC, CAC	Drive: FWD RWD SFI, EGR, HO2S(2), TWC(2)	
	(use abbreviations per SA	E J1930 SEP91)

Engine Code/ (also list CA/ 49S/ 50ST)	Vehicle Models (if coded see attachment)	Trans. (M5, A4 etc.)	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic converter part No.
3	JZA80L-ALPVZA JZA80L-AJPVZA	L4	3875	8.9	89661-14710	25620-46080	Front:M04 Rear :L08

Engine	Air aspiration system
code	Part No.
3	Turbocharger: 17201-46030 (Front) 17208-46030 (Rear) Charge air cooler: 46040

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

VEHICLE MODELS:

SUPRA JZA80L-ALPVZA JZA80L-AJPVZA

Page: 17.11-TTY3.0VJGKHK-1

Issued : 11/27/95 Rev. 1 : 12/05/95

17.11.00

E.O.# A-14-297

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

0.14

Manufacture	•	D. ()
Manufacturer: TOYOTA	Exh Eng Fam: TTY3.0VJGKHK	_ Evap Fam: TTY1095BYPA0
All Eng Codes in Eng Fam: CA	49S 50S x AB965	
Exh Std: CA Tier-1 x TLEV		DY 7
Evap std: 50K x Useful Life with		US EPA Tier-1 x
		Full In Use x Alt In Use
Veh Class(es): PC x LDT1	LDT2 MDV1 MDV2	MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam:	N/A (specify: N/A, I	DT1, MDV1, MDV2, MDV3, MDV4)
	ex-Fuel Dual-Fuel Bi	
_ CNG LNG		her(specify) Gasoline x Diesel
Emiss Test Fuel(s): Indo x Ph2	CNG LPG M85	
	R 2282 40 CFR 86.113-90	Other(specify)
	1	
ADMOC Town		her(specify)
	Equiv R/L Test	Proc: SHED Pt Source
D '	APU Cycle(e.g., Otto, Diesel, Tu	rbine):
Engine Configuration: I-6		Liters 182.9 / Cubic Inches
Valves per Cylinder: 4	Rated HP: 320	- State Interior
Engine: Front x Mid Rear		
Exhaust ECS(e.g., MFI, EGR, TC, CAC):	SELECT HOSE TWO TO	X 4WD-FT 4WD-PT
	SFI, EGR, HO2S(2), TWC(2), TO	C(2), CAC
	(use abbreviations per SAE	J1930 SEP91)

Continued on next page

: 17.11-TTY3.0VJGKHK-2

Issued 11/27/95