(Page 1 of 3)

#### State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER A-9-356-A Relating to Certification of New Motor Vehicles

#### CHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Chrysler Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: VCR24228G2JK <u>Displacement</u>: 4.0 Liters (242 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Warm Up Oxidation Catalytic Converter Three Way Catalytic Converter Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gas (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) TLEV certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	NMOG	_CO_	<u>NOx</u>	<u>нсно</u>	CO (20°F)
3751-5750	50,000	0.160	4.4	0.7	0.018	12.5
	100,000	0.200	5.5	0.9	0.023	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for NMOG reflect application of a 0.98 RAF for 1997 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	NMOG	<u></u>	<u>NOx</u>	НСНО_	CO (20°F)
3751-5750	50,000	0.077	1.0	0.1	0.002	2.3
	100,000	0.084	1.2	0.1	0.003	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this /9 day of November 1996.

R. B. Summerfield, Chief

Mobile Source Operations Division

E.O.	#	<u>A-9-</u>	356-7	
		Page	. 1 of	1

## 1997 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Chrysler Corporation Exh Eng Fam: VCR24228G2JK Evap Fam: VCR1049AYPON
All Eng Codes in Eng Fam: CA X 49S 50S AB965
Exh Std: CA Tier-1 TLEV_X LEV ULEV ZEV; US EPA Tier-1
Evap Std: 50K_X Useful Life with R/L In-Use Exh Std: Full In Use_X Alt In Use_
Veh Class(es): PCLDT1LDT2_X MDV1MDV2MDV3MDV4MDV5
Single Cert Std for Multi-Class Eng Fam: N/A (Specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated_X Flex-Fuel Dual-Fuel Bi-Level Gasoline_X Diesel
CNGLNGLPGM85Other (specify)
Emis Test Fuel(s): IndoPh2_X CNGLPGM85Other(specify)
Diesel: 13 CCR 2282 or 40 CFR 86.113-90 or 40 CFR 86.113-94
Service Accum: Std AMA Mod AMA X Mfr ADP Other (Specify)
NMOG Test Procedure: N/A Std Equiv X R/L Test Proce: SHED Pt Source
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine)
Engine Configuration: I-6 Displacement: / 4.0 Liters / 242 Cubic Inches
Valves per Cylinder: 2 Rated HP: 190 @ 4600 RPM
Engine: Front X Mid Rear Drive: FWD RWD 4WD-FT X 4WD-PT X
Exhaust ECS (eg., EGR, MFI, TC, CAC): WUOC. TWC. HO2S(2). OBD II. SFI (use abbreviations per SAE J1930 SEP91)

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type M5 A4	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Converter Part No.
CA-300 (CA)	XJJL72 XJJL74 XJUL74	A4	3750	3 E E	56041280AC	None	52021003 52101401
CA-500 (CA)	XJJL72 XJJL74		3750	T T A C			
				E D	,		
			·				

Date Issued: 10-16-96 - RC039TC

✓Revisions:	 	<del></del>	 -	

#### ATTACHMENT TO SDS PAGE 1 OF EXECUTIVE ORDER A-9-356-A

#### VEHICLE MODELS/CARLINE

Engine Family:

VCR24228G2JK

Evaporative Family:

VCR1049AYPON

Exhaust Control System:

WUOC, TWC, HO2S(2), OBD II, SFI

Evap. Control System:

Canister

Engine Displacement:

4.0L

Carline Model Code

Jeep® Cherokee 4WD

XJJL72, XJJL74, XJUL74

REPORT DATE: 10-16-96

#### ATTACHMENT TO SDS PAGE 1 OF EXECUTIVE ORDER A-9-356-A

1997 VCR24228G2JK

#### Chrysler Corporation Family Tire Usage

### LOADED VEHICLE WEIGHT

											COAST		TIRE			രാഥ ന	ELECTRIC	DYNC	COEFF	ICIENT	s	
			λ		MKT	LVW	TIRE	DES	RIPT	ION		*DYNO			TARGET		c		T A	В		С
MODEL	ENG	TRANS										HP					COEFFS, L	INE 2	IS 50	DEG W	HEN	NEEDED)
			-											_		 						
XJJL73	ERH	DGS 4A	Y	4850	С	3750	STD	97 11	L TZ	λ	12.20	14.0	33 3	3								
							OPT	97 T	16 TZ	A	11.92	14.4	33 3	3								
							OPT	97 TI	V TZ	λ	11.13	13.5	33 3	3								
XJJL72	ERH	DGS 4P	Y	4850	C	3750	STD	97 TI	C TZ	А	11.72	14.6	33 3	3								
							OPT	97 11	L TZ	A	12.20	14.0	33 3	3								
XJJL72	RRH	DGS 4W	Y	4850	С	3750	STD	97 TI	L TZ	X	12.20	14.0	33 3	3								
							OPT	97 17	6 TZ			14.4										
								97 17				13.5										
XJJL74	ERH	DGS 4A	Y	4900	C	3875						14.0										
								97 17				14.4										
								97 TI				13.5										
XJJL74	ERH	DGS 4P	Y	4900	С	3875						14.6										
								97 17				14.0										
XJJL74	ERH	DGS 4W	Y	4900	С	3075						14.0		-								
								97 17				14.4										
					_			97 17				13.5										
XJUL74	ERH	DGS 4W	Y	4900	C	3875						14.0										
					_			97 17	-			14.4									_	
203674	ERH	DGK 4A	Y	5300	C	4250		97 17				13.5										
								97 17	-			13.6			66 40		0.03664	51	R4	-1.226	R C	0.04786
							-	97 17				12.9			00.40		0.03004	-				
								97 17				13.1										
								97 T				12.8										
2,7,77,74	PDU	DGK 48	v	5300	С	4250						13.5										
	-	DOM: 12	•	3300	-			97 17				13.5										
								97 TI				13.6			66.40		0.03664	51	.84	-1.226	e (	0.04786
								97 17				12.9										
								97 17				13.1					i					
							OPT	97 T	R TZ	A	13.22	12.8	36 3	6			•					
ZJTL74	ERH	DGK RW	Y	5000	С	4000	STD	97 17	6 TZ		14.13	12.4	36 3	6								
			-		-			97 TI				12.2										
							OPT	97 TT	н та	λ	13.59	13.0	36 3	16								
							OPT	97 17	L TZ	A	14.52	12.2	36 3	16								
							OPT	97 TI	T TZ	A	13.75	12.3	36 3	6								

REPORT DATE: 10-16-96

CAR-TP01-