

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-254-46  
Relating to Certification of New Motor Vehicles

HYUNDAI MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Hyundai Motor Company exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: VHY2.0VJG2EK Displacement: 2.0 Liters (121.9 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Heated Oxygen Sensors (two)  
Three Way Catalytic Converters (two)  
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

The TLEV certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.085	0.7	0.1	0.0004	6.2
100,000	0.098	0.8	0.1	0.0005	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.


BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 19<sup>th</sup> day of June 1996.

  
R. B. Summerfield  
Assistant Division Chief  
Mobile Source Division

1997 AIR RESOURCES SUPPLEMENTAL DATA SHEET  
 PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer : Hyundai Motor CO Exh Eng Fam : VHY20VJG2EK Evap Fam : VHY1042BYMD4  
 All Eng Codes in Eng Fam : CA X 49S \_\_\_ 50S \_\_\_ AB965 \_\_\_  
 Exh Std : CA Tier-1 \_\_\_ TLEV X LEV \_\_\_ ULEV \_\_\_ ZEV \_\_\_ ; US EPA Tier-1 \_\_\_  
 Evap Std : 50K X Useful life with R/L \_\_\_ In-Use Exh Std : Full In Use X Alt In Use \_\_\_  
 Veh Class(es) : PC X LDT1 \_\_\_ LDT2 \_\_\_ MDV1 \_\_\_ MDV2 \_\_\_ MDV3 \_\_\_ MDV4 \_\_\_ MDV5 \_\_\_  
 Single Cert Std for Multi-Class Eng Fam : N/A (specify : N/A, LDT1, MDV1, MDV2, MDV3, MDV4)  
 Fuel Type(s) : Dedicated \_\_\_ Flex-Fuel \_\_\_ Dual-Fuel \_\_\_ Bi-Fuel \_\_\_ Gasoline X Diesel \_\_\_  
 CNG \_\_\_ LNG \_\_\_ LPG \_\_\_ M85 \_\_\_ Other (specify) \_\_\_  
 Emiss Test Fuel(s) : Indo X PH2 \_\_\_ CNG \_\_\_ LPG \_\_\_ M85 \_\_\_ other(specify) \_\_\_  
 Diesel : 13CCR 2282 \_\_\_ 40CFR 86.113-90 \_\_\_ 40CFR 86.113-94 \_\_\_  
 Service Accum : Std AMA X Mod AMA \_\_\_ Mfr ADV \_\_\_ OTHER(SPECIFY) \_\_\_  
 NMOG Test procedure : N/A \_\_\_ Std X Equiv \_\_\_ R/L Test Proc : SHED \_\_\_ Pt Source \_\_\_  
 Hybrid : Type A \_\_\_ B \_\_\_ C \_\_\_, APU Cycle(e.g., Otto, Diesel, Turbine) \_\_\_  
 Engine Configuration : I-4 Displacement : 2.0 / \_\_\_ Liters 121.9 / \_\_\_ Cubic Inches  
 Valves Per Cylinder : 4 Rated HP : 125 @ 5800 RPM  
 Engine : Front X Mid \_\_\_ Rear \_\_\_ Drive : FWD X RWD \_\_\_ 4WD-FT \_\_\_ 4WD-PT \_\_\_  
 Exhaust ECS (e.g., MFI , TC, CAC) . : HO2S(2) + TWC(2) + SFI + OBD II  
 (use abbreviations per SAE J1930 SEP91)

Eng. Code (list CA/ 49ST/50ST)	Veh. Models (If Coded see Attachment)	Trans. Type : L-Auto. M-Man.	Equiv. Test Weight	DPA or RLHP	Ign. Sys. (ECM/PCM) part No.	Catalyst Part No.
ACM5-Z /CM5-Z (CA)	SONATA	M5	3250	8.0	39110-33390 (CLSD12) or 39110-33395 (CLSD12)	28530-33600 & 28950-33750
ACL4-Z /CL4-Z (CA)		L4	↑	8.4	↑	↑

Issued : 5-1-96

Revised :