

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-420
Relating to Certification of New Motor Vehicles

CHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Chrysler Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: XCRXT0242230 Displacement: 4.0 Liters (242 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Three Way Catalytic Converter
Dual Warm Up Oxidation Catalytic Converters
Dual Heated Oxygen Sensors (two)
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gas (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) LEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Loaded Vehicle Weight (lbs.)</u>	<u>Miles</u>	<u>NMOG</u>	<u>CO</u>	<u>NOx</u>	<u>HCHO</u>	<u>CO (20°F)</u>
3751-5750	50,000	0.100	4.4	0.4	0.018	12.5
	100,000	0.130	5.5	0.5	0.023	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for NMOG reflect application of a 0.94 RAF for 1999 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

<u>Loaded Vehicle Weight (lbs.)</u>	<u>Miles</u>	<u>NMOG</u>	<u>CO</u>	<u>NOx</u>	<u>HCHO</u>	<u>CO (20°F)</u>
3751-5750	50,000	0.069	1.6	0.2	0.001	8.2
	100,000	0.093	2.6	0.2	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 8th day of July 1998.



R. B. Summerfield, Chief
Mobile Source Operations Division

1999 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
 PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

E.O. # A-9-420

Page 1 of 1

Manufacturer: Chrysler Corporation Exh Eng Fam: XCRXT0242230 Evap Fam: XCRXE0101G2S
 All Eng Codes in Eng Fam: CA X 49S 50S AB965 ORVR: YES NO X
 Exh Std: CA Tier-1 TLEV LEV X ULEV SULEV ; US EPA Tier-1
 Veh Class(es): PC LDT1 LDT2 X MDV1 MDV2 MDV3 MDV4 MDV5
 Single Cert Std for Multi-Class Eng Fam: N/A (Specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
 Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Level Gasoline X Diesel
 CNG LNG LPG M85 Other (specify)
 Exh. Emis Test Fuel(s): Indo CBG X CNG LPG M85 Other(specify)
 Diesel: 13 CCR-2282 or 40 CFR 86.113-90 or 40 CFR 86.113-94
 Evaporative Emission Test Procedure: California Federal X
 Service Accum: Std AMA Mod AMA X Mfr ADP Other (Specify)
 NMOG Test Procedure: N/A Std Equiv X R/L Test Proce: SHED Pt Source X
 Engine Configuration: I-6 Displacement: / 4.0 Liters / 242 Cubic Inches
 Valves per Cylinder: 2 Rated HP: 195 @ 4600 RPM
 Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT X 4WD-PT
 Exhaust ECS (eg., EGR, MFI, TC, CAC): 2WUOC, TWC, 2H02S(2), OBD II, SFI
 (use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type	ETW	DPA	Ignition	EGR	Catalyst
		M5 A4	or Test Wt.	or RLHP	(ECM/PCM) Part No.	System Part No.	Converter Part No.
CA-100 (CA)	WJTL74	A4	4000	S	56041424AE	None	52101391 52101091AB
	WJUL74		4250	E			
				A T T A C H E D			

Date Issued: 06/23/98

Revisions: _____

MODELS COVERED BY CERTIFICATE

Vehicle MFR: CHRYSLER Engine Family: XCRXT0242230 Certificate #:
Evaporative Fam: XCRXE010162S

Model ID	Car Line	California Sales
WJLL74	Grand Cherokee 2WD	YES
WJLL74	Grand Cherokee 4WD	YES

Model Codes

XJ J L 74

---Body Style
72=2 door
74=4 door
77=open

..... Trim Level
L=Covers all trim levels

----- Steering and Drive Line
B=Right Hand Steering, 2 wd-rear
U=Right Hand Steering, 4 wd
J=Left Hand Steering, 4 wd
T=Left Hand Steering, 2 wd-rear

----- Car Line
XJ=Cherokee
YJ=Wrangler
ZJ=Grand Cherokee

TJ=Wrangler(after 1996)
MJ=Grand Cherokee(after 1998)

ATTACHMENT TO SDS PAGE 1
OF EXECUTIVE ORDER A-9-420

1999
XCRXT0242230

Chrysler Corporation
Family Tire Usage

LOADED VEHICLE WEIGHT

MODEL	ENG	TRANS	A C	MKT GVW	LVW TYPE	ETW	TIRE DESCRIPTION USE YR COD MFG OPT	COAST DOWN TIME	*DYNO HP	TIRE PRES F R	COLD CO ELECTRIC DYNO COEFFICIENTS			
											TARGET A (LINE 1 IS 20 DEG	B COEFFS, LINE 2 IS 50 DEG	WHEN NEEDED	
WJL74	ERH	DGK	4A	Y	5350	C	4250	STD 99 TRY TZA	13.16	14.3	33 33	59.46	0.03847	
											54.05	0.03497		
								OPT 99 TR7 TZA	13.16	14.3	33 33	59.46	0.03847	
											54.05	0.03497		
WJL74	ERH	DGK	4B	Y	5350	C	4250	STD 99 TRY TZA	13.10	13.7	33 33	66.77	0.03908	
											60.70	0.03553		
								OPT 99 TTB TZA	12.44	14.4	33 33	66.77	0.03908	
											60.70	0.03553		
WJL74	ERH	DGK	4B	Y	5350	C	4250	STD 99 TRY TZA	12.19	14.0	33 33	59.90	0.03749	
											59.19	0.03337		
								OPT 99 TR7 TZA	13.10	13.7	33 33	59.19	0.03337	
											59.19	0.03337		
WJL74	ERH	DGK	RW	Y	5150	C	4000	STD 99 TRY TZA	12.71	13.2	33 33	72.92	0.03583	
											66.29	0.03257		
								OPT 99 TTB TZA	11.98	13.8	33 33	78.39	0.03831	
											71.26	0.03483		
WJL74	ERH	DGK	RW	Y	5150	C	4000	STD 99 TRY TZA	13.90	12.8	33 33	54.52	0.03368	
											49.56	0.03062		
								OPT 99 TR7 TZA	13.90	12.8	33 33	54.52	0.03368	
											49.56	0.03062		
WJL74	ERH	DGK	RW	Y	5150	C	4000	STD 99 TRY TZA	13.13	13.0	33 33	60.72	0.03466	
											55.20	0.03151		
								OPT 99 TTB TZA	13.13	13.0	33 33	60.72	0.03466	
											55.20	0.03151		
WJL74	ERH	DGK	RW	Y	5150	C	4000	STD 99 TRY TZA	12.79	12.3	33 33	66.28	0.03424	
											60.26	0.03113		

REPORT DATE: 04/30/98