

Pelle

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-836
Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Ford Motor Company exhaust emission control systems are certified as described below for light-duty trucks:

Emission Standard Category: Low Emission Vehicle (LEV)

Fuel Type (Certification Fuel): Gasoline (Indolene)

Engine Family: XFMXT04.01G5 Displacement: 4.0 Liters (244 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Dual Three Way Catalytic Converters
- Three Way Catalytic Converters (two)
- Dual Heated Oxygen Sensors (two)
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gas (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) TLEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Loaded Vehicle Weight (lbs.)</u>	<u>Miles</u>	<u>NMOG</u>	<u>CO</u>	<u>NOx</u>	<u>HCHO</u>	<u>CO (20°F)</u>
0-3750	50,000	0.075	3.4	0.2	0.015	10.0
	100,000	0.090	4.2	0.3	0.018	n/a

The TLEV certification exhaust emission values for this engine family in grams per mile are:

<u>Loaded Vehicle Weight (lbs.)</u>	<u>Miles</u>	<u>NMOG</u>	<u>CO</u>	<u>NOx</u>	<u>HCHO</u>	<u>CO (20°F)</u>
0-3750	50,000	0.046	1.1	0.1	0.001	5.4
	100,000	0.056	1.6	0.1	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 8th day of January 1999.

A handwritten signature in cursive script, reading "R. B. Summerfield". The signature is written in black ink and is positioned above the typed name and title.

R. B. Summerfield, Chief
Mobile Source Operations Division

1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Ford Motor Company Exhaust Engine Family: XFMXT04.01G5
 Engine Codes in EF: EDST
 Evap Standard: 50K ___ Useful Life with R/L X Evap Family: XFMXE0105BBE *ORVR: No*

Exhaust Std: Tier 0 ___ Tier 1 ___ TLEV ___ LEV X ULEV ___ ZEV ___ ; EPA Tier 0 ___ Tier 1 ___

Vehicle Class(es): PC ___ LDT1 X LDT2 ___ MDV1 ___ MDV2 ___ MDV3 ___ MDV4 ___ MDV5 ___

Single Cert Std for Multi-Class Eng Fam: N/A (specify N/A, LDT1, MDV1, MDV2, MDV3, MDV4)

Exh Cert Fuel(s): Indo X Ph2 ___ Diesel: 13 CCR 2282 ___ or 40 CFR 86.113-90 ___ or -94 ___
 M85 ___ CNG ___ LPG ___ Other (specify) _____

Fuel Type(s): Dedicated X Flex-Fuel ___ Dual-Fuel ___ Gasoline X Diesel ___ M85 ___
 CNG ___ LNG ___ LPG ___ Other (specify) _____ *NMOG Test Proced Std*

Hybrid: Type A ___ B ___ C ___ APU Cycle (e.g., Otto, Diesel, Turbine) _____

Engine Config: V-6 Liter (CID): 4.0 *Evap Test Procedure: Federal*
 Values per Cyl: 2 *(244) Service Accum: Mfr ADP* Rated HP: 160 @ 4200 rpm
 Engine: Front X Mid ___ Rear ___ Drive: FWD ___ RWD X 4WD-FT ___ 4WD-PT ___

Exhaust ECS & Special Features: 2TWC, TWC(2), 2HP25(2), SF1
 (Use abbreviations per SAE J1930, Sep 91)

Engine Code	Vehicle Models	Trans.	ETW	DPA (A/N)	Ignition (PCM) Part No. -12A650-	EGR System Part No. -9D475-	Catalyst Part No.
9LTABCG(A/N)	Ranger 4X2	A5	3500	-/11.3	XL5F-BBA	N/A	XL54-5F250-BO XL54-5E212-DO
	Ranger 4X2	A	3625	12.4/11.3	XL5F-BBA	N/A	XL54-5F250-BO XL54-5E212-DO
	Mazda 4X2	A	3500	-/11.3	XL5F-BBA	N/A	XL54-5F250-BO XL54-5E212-DO
	Mazda 4X2	A	3625	12.4/11.3	XL5F-BBA	N/A	XL54-5F250-BO XL54-5E212-DO