State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-848
Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Ford Motor Company exhaust emission control systems are certified as described below for medium-duty vehicles:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: XFMXA05.4HGC Displacement: 5.4 Liters (326 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Three Way Catalytic Converters (two)
Dual Heated Oxygen Sensors (two)
Exhaust Gas Recirculation
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gas (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) LEV certification exhaust emission standards for this engine family in grams per mile are:

Test Weight (lbs.)	Miles	NMOG	CO	NOx	HCHO	CO (20°F)
3751-5750	50,000	0.160	4.4	0.4	0.018	12.5
	120,000	0.230	6.4	0.6	0.027	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for NMOG reflect application of a 0.94 RAF for 1999 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Test Weight (lbs.)	Miles	NMOG	CO	NOx	HCHO	CO (20°F)
3751-5750	50,000	0.085	1.6	0.1	0.001	5.4
	120,000	0.119	3.0	0.2	0.002	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the medium-duty vehicle phase-in requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" (Title 13, California Code of Regulations, Section 1960.1(h)(2)).

BE IT FURTHER RESOLVED: That under the submitted medium-duty vehicle phase-in compliance plan, if the manufacturer incurs "Vehicle Equivalent Debits" for the aforementioned model year due to the manufacturer's failure to produce and deliver for sale in California the equivalent quantity of medium-duty vehicles certified to low-emission vehicle and/or ultra-low-emission vehicle exhaust emission standards required by the above-referenced standards and test procedures, all "Vehicle Equivalent Debits" incurred by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 12th day of June 1998.

R. B. Summerfield, Chief
Mobile Source Operations Division

1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer Ford Motor Company Exh. Eng. Fam.: XFMXA05.4HGC Evap. Fam.: XFMXE0155BAF/BAG

Engine Code Types: CA XXX 49S___ 50S___ ORVR: Yes___ No XXX

Exhaust Std: CA Tier-1___ TLEV___ LEV XXX ULEV___ ZEV___ U.S. EPA TIER-1___

Vehicle Class(es): PC___ LDT1___ LDT2___ MDV1___ MDV2 XXX MDV3___ MDV4___ MDV5___

Single Cert Std for Multi-Class Eng Fam: ___ (specify: N/A,LDT1,MDV1,MDV2,MDV3,MDV4)

Exhaust Emiss. Test Fuel: Indolene Clear _ CBG XXX Fuel Type: Gasoline XXX

Evaporative Emission Test Procedure: California___ Federal XXX

Service Accumulation: Std AMA___ Mod AMA___ Mfr ADP XXX Other___

NMOG Test Procedure: N/A___ Std XXX Equiv___ R/L Test Procedure: SHED___ Pt.Source XXX

Engine Configuration V-8 Displacement: 5.4 L (326 in³)

Valves/Cyl: 02 Rated HP: 235 @ 4250 RPM

Engine: Front XXX Mid___ Rear___ Drive: Fwd___ RWD XXX 4WD-FT___ 4WD-PT XXX

Exhaust Control System and Special Features 2TWC(2),2HO2S(2),EGR,SFI
(Use abbreviations per SAE J1930 SEP91)

EngineCode (California)	Vehicle Models	Trans. A-Auto M-Man	ETW	DPA	Ignition Part No (PCM)	EGR System Part No	Catalytic Converter Part No
9VZABCB A/N		A4			XL3F-AKB	F75E-CA	XL34-5E214-GA(LH) XL34-5G218-GA(RH)
	F150 4X2 RKS		5250	*			
	F150 4X2 RKL (6050 GVW)		5250				
	(6600 GVW)		5500				
	F150 4X2 SKS		5500				
	F150 4X2 SKL		5500				
	F150 4x4 RKS		5500				
	F150 4X4 RKL		5500				
9VZABUC A/N					XU2F-BA	"	"
	F150 4X2 RKL		5250				
	F150 4X2 SKS		5500				
	F150 4X4 RKL		5500				

* See Section 20.09.17.03 F 150 Pick up

EO# A-10-848
2 of 2

Supplemental Data Sheet
DPA Summary

Body	Trans	Tire	ETW	non-A/C DPA	A/C DPA
(4X2) RKL/RKS					
	4R100	P235	4500	15.0	16.4
			4750	15.0	16.4
		$	5250	15.0	16.4
		$	5500	14.1	15.5
		P255	4500	14.5	15.9
			4750	14.5	15.9
		$	5250	14.5	15.9
		$	5500	14.5	15.9
		LT245	4500	13.3	14.7
			4750	13.3	14.7
		$	5250	13.3	14.7
		$	5500	13.3	14.7
(4X2) SKS/SKL					
	4R100	P235	5000	15.7	17.1
		*	5250	15.7	17.1
		$	5500	15.7	17.1
		P255	5000	15.1	16.5
		*	5250	15.1	16.5
		$	5500	15.1	16.5
		LT245	5000	13.7	15.1
		*	5250	13.7	15.1
		$	5500	13.7	15.1

Body	Trans	Tire	ETW	non-A/C DPA	A/C DPA
(4X4) RKS					
	4R100	P 235	4750	17.2	18.6
			5000	17.2	18.6
			5250	17.2	18.6
			5500	17.2	18.6
		$	6000	17.2	18.6
		Other P-met	4750	18.7	20.1
			5000	18.7	20.1
			5250	18.7	20.1
			5500	18.7	20.1
		$	6000	18.7	20.1
		LT 245	4750	16.0	17.4
			5000	16.0	17.4
			5500	16.0	17.4
		$	6000	16.0	17.4
			5500	15.6	17.0
(4X4)					
			5250	16.6	18.0
			5250	15.3	16.7
		$	6000	15.3	16.7
		LT 245	4750	15.4	16.8
			5500	15.4	16.8
		LT 265	4750	15.0	16.4
			5000	15.0	16.4
			5250	15.0	16.4
			5500	15.0	16.4
		$	6000	15.0	16.4

* - ETW/ALVW
$ - ALVW

ENGINE FAMILY: XFMXA05.4HGC
ISSUED:
REVISED: JUN 03 1998