State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-259-67 Relating to Certification of New Motor Vehicles

SUZUKI MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Suzuki Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

<u>Fuel Type</u>: Gasoline

Engine Family: XSKXV1.30LNA Displacement: 1.3 Liters (79 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Three Way Catalytic Converter Warm Up Three Way Catalytic Converter Heated Oxygen Sensors (two)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

_Miles	Non-Methane <u>Organic Gas</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon <u>Monoxide {20°F)</u>
50,000	0.075	3.4	0.2	0.015	10.0
100,000	0.090	4.2	0.3	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.94 RAF for 1999 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Carbon <u>S Organic Gas Monoxide</u>		Nitrogen Oxides	Formaldehyde	Carbon <u>Monoxide (20°F)</u>	
50,000	0.055	1.2	0.2	0.001	4.9	
100,000	0.077	1.8	0.3	0.001	n/a	

SUZUKI MOTOR CORPORATION

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year. SUZUKI MOTOR CORPORATION

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this _____ day of June 1998.

R.B. Summerfield, Chief V Mobile Source Operations Division

MAY.15.1998	10:13AM AMER	ICAN SU	ZUKI 71	4-970 60	aas	NO.176	5 P.16/22
	1999 Modi Passenge	EL YEAR A ER CARS, I	IR RESOUT	RCE BOAR	D SUPPLEMENTAL DAT, AND MEDIUM DUTY VE		17-K-1 D.# <u>A-259-67</u> Page 1 of 1
Exh Std; Tier 0 EVAP Std : 50K Veh Class(es): PC, Single Cert Std for I Fuel Type (s): Dedi CN Emiss Test Fuel (s); EVAP Emission Tes Service Accum: NMOG Test Procede Hybrid: Type A Engine configuration Valves per Cylinder: Engine: Front _X Exhaust ECS (eg., E	UKI MOTOR COF Eng Fam: CA_X Tier 1TLEV Useful Life with I X_LDT1LDT2_ Multi-Class Eng Fan cated_XFlex-I IndoPh2_X_C Diesel: 13CCR 228: t Procedures: Califi Std AMAN BC BC Mid	LEV_X_L 49S5/ LEV_X_L R/L_X MDV n: <u>N/A</u> (g Fuel LPG NG ornia: 2 od AMA Std APU accement: Ra Driv	Exh Eng OS JLEV 1 MD\ specify: N Dual-f M8: LPG 40CFF Cycle (e. 1.3 Liter ated HP /e: FWD FL/ HO25	Fam: X: ORVI In Usi /2N /A, LDT1, ⁵ uel N85 86.113-9 Mfr ADI Equiv Rotto, E s or _79 79 @	SKXV1.30LNA R: YESXN /; US El e Exh Std: FULL in U /DV3MDV4 LDT2,MDV1,MDV2 BI-FuelGasofinither (specify) Other (specify) Other (specify) 0040CFF alX PXOther (specify) Other (specify) QO QO	EVAP Fam:X O se A MDV5 MDV3,MDV4, a _X_Diesel 866.113-94 cify) Pt	Tier 1 Vt In UseX MDV5) SourceX
Engine Code (also list CA/49ST/50ST)	Vehicle Models (re: p.21.00)	Trans type	ETW	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converters Part No.
CVŁKM (CA NY MA CT NJ RI VT)	Swift Hatchback Metro Hatchback Metro Sedan	M5	2250 2375	7.3	33920-52G40		
CVLKA (CA NY MA CT NJ RI VT)	Swift Hatchback Metro Hatchback	A3	2250	7.0	33920-52G50	N/A	14150-51G00 14150-50G20
	Metro Sedan	[2375	7.0			

(⁶)	Date (ssued: Revised:	17MAR98 01MAY98 (R1)
	Revised: Processed by:	date:Reviewed By:Dete:

\\SUZUKIHQ1\GOVTLEGL\CERT\LD99\app-PC\R1\Px17kj2eos87.R1.doc

•