## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-14-353 Relating to Certification of New Motor Vehicles

## TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for lightduty trucks:

Fuel Type: Gasoline

1 a a t

Engine Family: XTYXTO2.7BBP Displacement: 2.7 Liters (164 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converter Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle		Non-Methane	Carbon	Oxides of	Carbon	
Weight (lbs.) Miles		Hydrocarbons	<u>Monoxide</u>	<u>Nitrogen</u>	<u>Monoxide (20°F)</u>	
3751-5750	50,000	0.32	4.4	0.7	12.5	
	100,000	0.40	5.5	0.97	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle		Non-Methane	Carbon	Oxides of	Carbon	
_Weight (lbs.)Miles		<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Nitrogen</u>	<u>Monoxide (20°F)</u>	
3751-5750	50,000	0.09	1.6	0.1	5.5	
	100,000	0.10	1.9	0.12	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gases (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles." TOYOTA MOTOR CORPORATION

. '

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this \_\_\_\_\_ day of August 1998.

R. B. Summerfield, Chref

Mobile Source Operations Division

## 17.11.00

. •

14 - 353E.O.#\_

Page

1999 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES					
Manufacturer: <u>TOYOTA</u> Exh Eng Fam: <u>XTYXT02,7BBP</u> Evap Fam: <u>XTYXE0095AE0</u>					
All Eng Codes in Eng Fam: CA 49S 50S _x AB965, ORVR: YES NO _x					
Exh Std: CA Tier-1 x TLEV LEV ULEV SULEV , US EPA Tier-1 x					
Veh Class(es): PC LDT1 LDT2 _x MDV1 MDV2 MDV3 MDV4 MDV5					
Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)					
Fuel Type(s): Dedicated <u>x</u> Flex-Fuel Dual-Fuel Bi-Fuel Gasoline <u>x</u> Diesel					
CNG LNG LPG M85 Other (specify)					
Exh Emiss Test Fuel(s): Indo x CBG CNG LPG M85 Other (specify)					
Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94					
Evaporative Emission Test Procedure: California Federal _x					
Service Accum: Std AMA Mod AMA Mfr ADP Other (specify)					
NMOG Test Procedure: N/A x Std Equiv R/L Test Proc: SHED x Pt Source					
Engine Configuration: <u>I-4</u> Displacement: <u>2.7 Liters</u> <u>164.4 Cubic Inches</u>					
Valves per Cylinder: 4 Rated HP1: 150@4800 RPM					
Engine: Front <u>x</u> Mid <u>Rear</u> Drive: FWD <u>RWD <u>x*1</u> 4WD-FT 4WD-PT <u>x*2</u></u>					
Exhaust ECS (e.g., MFI, EGR, TC, CAC): SFI,EGR.HO2S(2),TWC					
(use abbreviations per SAE J1930 JUN93)					

Note \*1 : Applied to truck line 4RUNNER 2WD.

Note \*2 : Applied to truck line 4RUNNER 4WD.

Note \*3 : Applied to truck line TAOYOTA TACOMA 4WD

Engine		Trans	FTW				
(also list		(M5,	or		Ignition		Catalytic
CA/49S/	Vehicle Models	A4,	Test	DPA or	(ECM/PCM)	EGR system	Converter
50ST	(if coded see attachment)	etc.)	Wt	RLHP	Part No.	Part No.	Part No.
1	RZN180L-GKMSKA	M5	3750	11.3/12.1	89661-3D620*1	25620-75040	S92*1*2
	RZN185L-GKMSKA		4000	12.2/13.	89661-3D640*2		S93*3
2	RZN180L-GKMSKA		3875	12.4/13.3			
	RZN185L-GKMSKA	1	4250	13.4/15.3			
3	RZN171L-CRPDKAB	L4	3750	13.6/13.9/14.0	89661-3D630*1	25620-75050	
	RZN180L-GKPSKA		3875	11.3/12.1	89661-3D650*2		
	RZN185L-GKPSKA	]	4250	12.2/13.9	89661-04500*3		
4	RZN171L-CRPDKAB	]	3875	15.0/15.3/15.4			
	RZN180L-GKPSKA	]		12.4/13.3	]		
	RZN185L-GKPSKA	]	4250	13.4/15.3			

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

17.11.00

۲

A-14-353 E.O.#

Page\_

1999 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: <u>TOYOTA</u> Exh Eng Fam: <u>XTYXT02.7BBP</u> Evap Fam: <u>XTYXE0095AE0</u>

VEHICLE MODELS:

4RUNNER 2WD	4RUNNER 4WD	TOYOTA TACOMA 4WD
RZN180L-GKMSKA RZN180L-GKPSKA	RZN185L-GKMSKA RZN185L-GKPSKA	RZN171L-CRPDKAB