State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-193 Relating to Certification of New Motor Vehicles

DAIMLERCHRYSLER AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year DaimlerChrysler AG exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline (Indolene)

Engine Family: YMBXV06.0GNU Displacement: 6.0 Liters (365 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Secondary Air Injection Dual Heated Oxygen Sensors (two) Dual Three Way Catalytic Converters

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20°F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20°F)</u>
50,000	0.20	0.9	0.1	3.3
100,000	0.20	1.0	0.1	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and Executed at El Monte, California this 28^{tl} day attachment.

R. B. Summerfield, Chief

Mobile Source Operations Division

2000 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: DaimlerChrysler AG Exh. Engine Family: YMBXV06.0GNU Evap. Family: YMBXR0155MYZ All Eng. Codes in Eng. Fam.: CA 49S 50S X AB965 OVRV Yes X NO Exh. Std.: CA Tier-1 x TLEV LEV ULEV SULEV US EPA Tier-1 x Veh. Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5 Single Cert. Std. for Multi-Class Eng. Fam.: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4) MDV4 MDV5 MDV4 MDV5 MDV4 MDV5 MDV4 MDV4 MDV5 MDV4
Exh. Std.: CA Tier-1 x TLEV LEV ULEV SULEV USEPA HeIT X Veh. Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5 Single Cert. Std. for Multi-Class Eng. Fam.: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4) MDV4 MD
Veh. Class(es):PC X LDT1LDT2MDV1MDV2MDV3MDV4MDV3Single Cert. Std. for Multi-Class Eng. Fam.:N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)Fuel Type(s):Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X DieselCNG LNG LPG M85 Other (specify)Emiss. Test Fuel(s):Indo x CBG CNG LPG M85 Other (specify)Diesel:13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94Evaporative Emmision Test Procedure:California Federal XService Accum:Std. AMA X Mod. AMA Mfr ADP Other (specify)NMOG Test Procedure:N/A x Std. Equiv R/L Test Proc.: SHED X Pt SourceEngine Configuration:V-12 Displacement: 6.0 Liters 365 Cubic InchesValves per Cylinder:4 Rated HP: 389@5200 RPM
Single Cert. Std. for Multi-Class Eng. Fam.: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MD
Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify) Emiss. Test Fuel(s): Indo x CBG CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94 Evaporative Emmision Test Procedure: California Federal X Service Accum: Std. AMA X Mod. AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A x Std. Equiv R/L Test Proc.: SHED X Pt Source Engine Configuration: V-12 Displacement: 6.0 Liters 365 Cubic Inches Valves per Cylinder: 4 Rated HP: 389@5200 RPM
Emiss. Test Fuel(s): Indo x CBG CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94 Evaporative Emmision Test Procedure: California Federal X Service Accum: Std. AMA X Mod. AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A x Std. Equiv R/L Test Proc.: SHED X Pt Source Engine Configuration: V-12 Displacement: 6.0 Liters 365 Cubic Inches Valves per Cylinder: 4 Rated HP: 389@5200 RPM
Emiss. Test Fuel(s): Indo x CBG CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94 Evaporative Emmision Test Procedure: California Federal X Service Accum: Std. AMA X Mod. AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A x Std. Equiv R/L Test Proc.: SHED X Pt Source Engine Configuration: V-12 Displacement: 6.0 Liters 365 Cubic Inches Valves per Cylinder: 4 Rated HP: 389@5200 RPM
Evaporative Emmision Test Procedure: California Federal X Service Accum: Std. AMA X Mod. AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A x Std. Equiv R/L Test Proc.: SHED X Pt Source Engine Configuration: V-12 Displacement: 6.0 Liters 365 Cubic Inches Valves per Cylinder: 4 Rated HP: 389@5200 RPM
Evaporative Emmision Test Procedure: California Federal X Service Accum: Std. AMA X Mod. AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A x Std. Equiv R/L Test Proc.: SHED X Pt Source Engine Configuration: V-12 Displacement: 6.0 Liters 365 Cubic Inches Valves per Cylinder: 4 Rated HP: 389@5200 RPM
Service Accum: Std. AMA X Mod. AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A x Std. Equiv R/L Test Proc.: SHED X Pt Source Engine Configuration: V-12 Displacement: 6.0 Liters 365 Cubic Inches Valves per Cylinder: 4 Rated HP: 389@5200 RPM Widdle Rear Drive: FWD RWD X 4WD-FT 4WD-PT
NMOG Test Procedure: N/A x Std. Equiv R/L Test Proc.: SHED X PT Solice Engine Configuration: V-12 Displacement: 6.0 Liters 365 Cubic Inches Valves per Cylinder: 4 Rated HP: 389@5200 RPM Widdle Rear Drive: FWD RWD X 4WD-FT 4WD-PT
Engine Configuration: V-12 Displacement: 6.0 Liters 365 Cubic inches Valves per Cylinder: 4 Rated HP: 389@5200 RPM Valves per Cylinder: FWD RWD X 4WD-FT 4WD-PT
Valves per Cylinder: 4 Rated HP: 389@5200 Total Rated HP: 389@5200 T
- Middle Rear Drive: FWD KWD X 4WD-1 - TIPE TO THE TOTAL
English.
Exhaust ECS (eg., MFI, EGR, TC, CAC): SFI / AIR / / 2H02S (2) / 2 TWC (use abbreviations per SAE J1930 JUN93)
(use abbreviations per SAE 3 1930 30 N33)
Engine Code Vehicle Models Trans. Type ETW DPA Ignition EGR Catalytic
Engine Code Vehicle Models Halls. Type Converter Converter Converter
(also list (in coded see (A., in your part No. Part No. Part No.
CA/4951/3031 Attachment/
M 120-5 SL 600 L-5 4 750 8.2 A0235450732 (left)
A1294904814
(right)
Date Issued: Revisions: