

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-872
Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Ford Motor Company exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: YFMXV02.5VBC

Displacement: 2.5 Liters (152.5 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Dual Three Way Catalytic Converters
- Dual Heated Oxygen Sensors (two)
- Three Way Catalytic Converter
- Exhaust Gas Recirculation
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.13	0.8	0.1	4.1
100,000	0.16	1.0	0.1	n/a

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235.)

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965.)

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."


BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model- Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 6 day of August 1999.


R. B. Summerfield, Chief
Mobile Source Operations Division

2000 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 1
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer FORD MOTOR COMPANY Exh. Eng. Fam.: YFMXV02.5V8C Evap. Fam.: YFMXR0115BBE
 Engine Code Types: CA 49S 50S XX AB965 ORVR: Yes XX No
 Exhaust Std: CA Tier-1 XX TLEV LEV ULEV ULEV SULEV U.S. EPA TIER-1
 Vehicle Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
 Fuel Type(s): Dedicated XX Flex-Fuel Dual-Fuel Bi-Fuel Gasoline XX Diesel
 CNG LNG LPG M85 Other (specify):
 Exh Emiss Test Fuel(s): Indo XX CBG CNG LPG M85 Other(specify):
 Diesel 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94
 Evaporative Emission Test Procedure: California Federal XXX
 Service Accum: Std AMA XX Mod AMA Mfr ADP Other (specify)
 NMOG Test Procedure: N/A XX Std Equip R/L Test Procedure: SHED Pt. Source XX
 Engine Configuration V-6 Displacement: 2.5L Liters 152.5 Cubic Inches
 Valves/Cyl: 4 Rated HP: 170 @ 6250 RPM
 Engine: Front XXX Mid Rear Drive: Fwd XX RWD 4WD-Ft 4WD-PT
 Exhaust: ECS (e.g., MFI, EGR, TC, CAC): 2TWC, TWC, 2 H025(2) EGR, SP1
 (Use abbreviations per SAE J1930 JUN93)

Engine Code/	Veh. Models	Trans. Type: A-Auto M-Man.	Equiv. Test Weight	DPA		Ign. Sys. (ECM/PCM) Part No. -12A650-	EGR Syst. Part No. -3D475-	Catalyst Part No. -5E212-
				#	\$			
2.5L	<i>Ford</i>							
9LCABCC N	CONTOUR	A4	3375	4.6	4.9	XS2A-HC	XL3E-DA	F7NV-CF
9LCABCC A	<i>Mercury</i>	A4	3375	5.1	5.4	"	(ALT)	"
9LCABCC N	MYSTIQUE	A4	3375	4.6	4.9	"	F53E-AA	F7NV-CF
9LCABCC A	<i>Mercury</i>	A4	3375	5.1	5.4	"	"	"
9LCABDC N	COUGAR	A4	3375 ^a		5.3	XS8A-HC	"	F7NV-CF
9LCABDC A	"	A4	3375 ^a		5.8	"	"	"
9LCMBCC N	CONTOUR	M5	3250	4.7	5.8	XS2A-FC	"	F7NV-CF
9LCMBCC A	"	M5	3250 ^a	5.2	6.4	"	"	"
9LCMBDC N	COUGAR	M5	3375		5.3	XS8A-FC	"	F7NV-CF
9LCMBDC A	"	M5	3375		5.8	"	"	"
9LCMBCC N	MYSTIQUE	M5	3250 ^a	4.7	5.8	XS2S-FC	"	F7NV-CF
9LCMBCC A	"	M5	3375	5.2	6.4	"	"	"
9LCMAHA N	CONTOUR SVT	M5	3375		5.3	XS2F-FA	"	F7NV-AB
9LCMAHA A	"	M5	3375		5.8	"	"	"

ⓐ Tested at next higher ETW
 # Base tire P195/65R14
 \$ Optional tire P205/60R15
 \$ Standard tire P215/50R16 on Cougar and Contour SVT

ENGINE FAMILY: YFMXV02.5V8C
 ISSUED: **JUN 30 1999**
 REVISED:

20.09.17.02 - 1