State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-259-74 Relating to Certification of New Motor Vehicles

SUZUKI MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Suzuki Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YSKXVI.30LNA <u>Displacement</u>: 1.3 Liters (79 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Three Way Catalytic Converter Warm Up Three Way Catalytic Converter Heated Oxygen Sensors (two)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.075	3.4	0.2	0.015	10.0
100,000	0.090	4.2	0.3	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane <u>Organic Gas</u>	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.055	1.2	0.2	0.001	4.9
100,000	0.077	1.8	0.3	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

R. B. Summerfield, Chief

Mobile Source Operations Division

2000 MODEL YEAR AIR RESOURCE BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer: SUZU	KI MOTOR CORP	E:	xh Eng Fa	am: YS	KXV1.30LNA E	VAP Fam: YS	KXR0085RMA
All Engine Codes in E	Eng Fam: CA49S	50S_	_XAB	965	ORVR: YES US EPA	NO	
					Exh Std: FULL In Use		
					DV3 MDV4		
Single Cert Std for M	ulti-Class Eng Fam:	NA (so	ecify: N/A	A. LDT1. I	_DT2,MDV1,MDV2,M	DV3.MDV4.MI	DV5)
Fuel Type (S): Dedica	atedXFlex-	Fuel	Dual-	Fuel	Bi-Fuel Gasolin	e X Diesel	
CNG	LNG	LPG	M85	Oth	er (specify)		
Emiss Test Fuel (s): I	ndo Ph2 _X_ CN	GL	PG	M85	Other (specify)		
					0 40CFR		
EVAP Emission Test							
Service Accum: S	Std AMA Mo	d AMA _		Mfr ADP	XOther (spec	cify)	
NMOG Test Procedu	re : N/A 5	Std	XE	quiv	R/L Test Proc: SH	ED Pt S	Source_X
Hybrid: Type A	_B, C,	APU (Cycle (e.g	g. Otto, Di	iesel, Turbine)		
Engine configuration:							
Valves per Cylinder: _	4	Rai	ted HP	79 <u>@6</u>	.000 RPM		
Engine: Front _X_	Mid Rear	Drive	e: FWD .	_ <u>X_</u> RW	/D 4WD-FT	4WD-PT_	
Exhaust ECS (eg., EC	SR, MFI, TC, CAC):						
			(per SAE	J1930 S	EP95)		
	T			· · · · · · · · · · · · · · · · · · ·			
Engine Code (also list CAV49ST/50ST)	Vehicle Models (re: p.21.00)	Trans type	ETW	RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converters Part No.
0.11.0.4			2022				
	Swift Hatchback Metro Hatchback	M5	2250	7.3	33920-52G40	1	
VT & NTR)							
V / W (/ / / /)	*						
	* Metro Sedan		2375	7.0			14150-51G00
						. N/A	14150-50G20
CVLKA	Swift Hatchback Metro Hatchback		2250	7.3	33920-52G50	IN/A	
(CA MA NY VT & NTR)		А3					
νιανιπ) .		•					
	[⊀] Metro Sedan		2375	7.0	-		

* Chevrolet Metro.

Date Issued: April 28,1999

Revised: