



(Page 1 of 3)

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-377
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YTYXT03.4FFR Displacement: 3.4 Liters (206 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converters (two)
Air Fuel Ratio Sensor
Heated Oxygen Sensor
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) LEV certification exhaust emission standards for this engine family in grams per mile are:

| <u>Loaded Vehicle Weight (lbs.)</u> | <u>Miles</u> | <u>NMOG</u> | <u>CO</u> | <u>NOx</u> | <u>HCHO</u> | <u>CO (20°F)</u> |
|-------------------------------------|--------------|-------------|-----------|------------|-------------|------------------|
| 3751-5750 | 50,000 | 0.100 | 4.4 | 0.4 | 0.018 | 12.5 |
| | 100,000 | 0.130 | 5.5 | 0.5 | 0.023 | n/a |

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gases (NMOG) reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

| <u>Loaded Vehicle Weight (lbs.)</u> | <u>Miles</u> | <u>NMOG</u> | <u>CO</u> | <u>NOx</u> | <u>HCHO</u> | <u>CO (20°F)</u> |
|-------------------------------------|--------------|-------------|-----------|------------|-------------|------------------|
| 3751-5750 | 50,000 | 0.060 | 0.8 | 0.2 | 0.001 | 5.5 |
| | 100,000 | 0.066 | 0.8 | 0.3 | 0.002 | n/a |

TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-14-377
(Page 2 of 3)

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-14-377
(Page 3 of 3)

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 17th day of December 1998



R. B. Summerfield, Chief
Mobile Source Operations Division

17.11.00

E.O.# A-14-377

Page 1

2000 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: YTYXT03.4FFR Evap Fam: YTYXE0145AE0
 All Eng Codes in Eng Fam: CA 49S 50S AB965 ORVR: YES NO
 Exh Std: CA Tier-1 TLEV LEV ULEV SULEV US EPA Tier-1
 Veh Class(es): PC LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
 Fuel Type(s): Dedicated Flex-Fuel Dual-Fuel Bi-Fuel Gasoline Diesel
 CNG LNG LPG M85 Other (specify) _____
 Exh Emiss Test Fuel(s): Indo CBG CNG LPG M85 Other (specify) _____
 Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94
 Evaporative Emission Test Procedure: California Federal
 Service Accum: Std AMA Mod AMA Mfr ADP Other (specify) _____
 NMOG Test Procedure: N/A Std Equiv R/L Test Proc: SHED Pt Source
 Engine Configuration: V-6 Displacement: 3.4 Liters 206 Cubic Inches
 Valves per Cylinder: 4 Rated HP: 190@4800 RPM
 Engine: Front Mid Rear Drive: FWD RWD 4WD-FT 4WD-PT
 Exhaust ECS (e.g., MFI, EGR, TC, CAC): SFI,A/F S(*1), TWC(2), HO2S
 (use abbreviations per SAE J1930 JUN93)

Note *1 : A/F S means Air-fuel ratio sensor.
 Note *2 : for TOYOTA TUNDRA 2WD.
 Note *3 : for TOYOTA TUNDRA 4WD.

| Engine Code (also list CA/49S/50ST) | Vehicle Models (if coded see attachment) | Trans. (M5, A4, etc.) | ETW or Test Wt | DPA or RLHP | Ignition (ECM/PCM) Part No. | EGR system Part No. | Catalytic Converter Part No. |
|-------------------------------------|---|-----------------------|----------------|----------------|-----------------------------|---------------------|------------------------------|
| 1 | VCK40L-ARMSKA VCK40L-TRMSKA | M5 | 4750 4500 | 15.6/15.9/16.0 | 89661-0C070 | N/A | Q11 |
| 2 | VCK40L-ARMSKA VCK40L-TRMSKA | | 4750 4500 | 17.0/17.3/17.4 | | | U93 |
| 3 | VCK40L-ARSSKA VCK40L-TRSSKA | L4 | 4750 4500 | 15.6/15.9/16.0 | 89661-0C080 | | |
| 4 | VCK40L-ARSSKA VCK40L-TRSSKA | | 4750 4500 | 17.0/17.3/17.4 | | | |
| 5 | VCK30L-ARMSKA VCK30L-TRMDKA | M5 | 4500 4250 | 14.3/15.1 | 89661-0C050 | | |
| 6 | VCK30L-ARMSKA VCK30L-TRMDKA | | 4500 4250 | 15.7/16.5 | | | |
| 7 | VCK30L-ARSSKA VCK30L-TRSDKA | L4 | 4500 4250 | 14.3/15.1 | 89661-0C060 | | |
| 8 | VCK30L-ARSLKA VCK30L-ARSSKA VCK30L-TRSDKA | | 4500 4250 | 15.7/16.5 | | | |

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

17.11.00

E.O.# A-14-377

Page 2

2000 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacture TOYOTA Exh. Eng. Fam YTYXT03.4FFR Evap. Fam YTYXE0145AE0

VEHICLE MODELS:

| <u>TOYOTA TUNDRA 2WD</u> | <u>TOYOTA TUNDRA 4WD</u> |
|--------------------------|--------------------------|
| VCK30L-ARMSKA | VCK40L-ARMSKA |
| VCK30L-ARSLKA | VCK40L-ARSLKA |
| VCK30L-ARSSKA | VCK40L-ARSSKA |
| VCK30L-TRMDKA | VCK40L-TRMSKA |
| VCK30L-TRSDKA | VCK40L-TRSSKA |