

*Fili*

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

**IT IS ORDERED AND RESOLVED:** That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	FUEL TYPE
2002	2FMXT05.4RF8	5,751 - 8,500 Pounds Adjusted Loaded Vehicle Weight Medium Duty Vehicle	Low Emission Vehicle (LEV)	Gasoline (Indolene)
No.	EVAPORATIVE FAMILY (EVAP)	No.	SPECIAL FEATURES & EMISSION CONTROL SYSTEMS (ECS)	* = not applicable
1	2FMXE0155BBF	1	2TWC(2), 2HO2S(2), EGR, SFI, OBD (P)	
2	2FMXE0155BBG	2	*	
3	2FMXE0155BAF	3	*	
4	2FMXE0155BAG	4	*	

TWC = 3-way catalytic converter    WUTWC = warm-up TWC    ADSTWC = adsorber TWC    OC = oxidation catalytic converter    O2S = oxygen sensor  
 HO2S = heated O2S    EGR = exhaust gas recirculation    AIR = secondary air injection    PAIR = pulsed AIR  
 MFI = multiport fuel injection    SFI = sequential MFI  
 TC/SC = turbo/super charger    CAC = charge air cooler  
 OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = series

EVAP No.	ECS No.	ENGINE SIZE (L)	VEHICLE MAKES & MODELS	VEHICLES SUBJECT TO SFTP STANDARDS ARE UNDERLINED	ABBREVIATIONS
1	1	5.4	Ford Expedition 2WD; Lincoln Blackwood 2WD		
2	1	5.4	Ford Expedition 2WD/4WD; Lincoln Navigator 2WD/4WD		
3	1	5.4	Ford F-150 Pickup 2WD/4WD Short Wheelbase, F-150 Supercrew Cab Pickup 4WD Short Wheelbase		
3	1	4.6	Ford F-150 Supercrew Cab Pickup 4WD Short Wheelbase		
4	1	5.4	Ford F-150 Pickup 2WD/4WD Long Wheelbase		

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]		NMOG [g/mi] @RAF = 1.00		CH4 = methane		NMOG = non-CH4 organic gas		NMHC = non-CH4 hydrocarbon		CO = carbon monoxide		NOx = oxides of nitrogen		HCHO = formaldehyde		PM = particulate matter		RAF = reactivity adjustment factor	
CERT	STD	CERT	STD	CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]							
*	*	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
K = 1000 miles	@ 50K	0.116	0.195	1.3	5.0	0.1	0.6	1	22	*	*	0.02	1.2						
	@ 120K	0.149	0.280	1.8	7.3	0.1	0.9	1	32	*	*	0.04	1.8						
	@ 50°F, 4K	*	*	*	*	*	*	*	*	*	*	*	*						

CO [g/mi] @ 20°F, 50K		g = gram mg = milligram mi = mile	NMHC+NOx [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	STD		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
4.5	12.5		*	*	*	*	*	*	*	*	*	*
F = degree Fahrenheit			@ 4K	*	*	*	*	*	*	*	*	*
			@ 120K	*	*	*	*	*	*	*	*	*


  

@ 120K	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.1	1.0	0.005	*	1.1	1.0	0.005	*	1.3	1.0	0.01	*	1.3	1.0	0.01	*
STD	2.0	2.5	0.05	*	2.5	3.0	0.05	*	2.0	2.5	0.05	*	2.5	3.0	0.05	*

2-D, 3-D [g/test] = 2-day, 3-day diurnal and hot-soak    RL [g/mi] = running loss    ORVR [g/gallon of fuel dispensed] = on-board refueling vapor recovery

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 20<sup>th</sup> day of June 2000.   
 R. B. Summerfield, Chief  
 Mobile Source Operations Division