

## **BAYERISCHE MOTOREN WERKE AG**

EXECUTIVE ORDER A-008-0159 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP				VEHICLE TYPE C=passenger car; LDT=light-duty DV=medium-duty vehicle; LVW=l vehicle weight; ALVW=adjusted I	y truck; CA loaded	ATEGORY vehicle; TL	MISSION STAND (LEV=low emis EV= transitional LEV EV; SULEV=super Ut	sion	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	3 3	3BMXT04.6XHP			N	IDV: 3,751 - 5,750 pounds A	ALVW		LEV		120K / 120K	OK Gasoline				
No.	EVAPORATIVE FAMILY (EVAF)				No.	SPECIAL FEAT EMISSION CONTROL	TURES & SYSTEMS (E	ECS)	* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	звмх	BMXR0160E39					02S(2), SFI, /		AF	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust						
2		•			2		*		gas	gas recirculation AiR/PAIR=secondary air Injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		*			3		*		TB	TBI= throttle body injection TC/SC=turbo /super charger						
4		*			4		*		CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
EVA		CS	ENGI			VEHICLE	VEHICLE	ES SUBJE	CT TO SFTP	4000						
No.	No.	o.	SIZE	(L)		MAKES & MODELS	STANDA	RDS ARE	UNDERLINED	ABB	REVIATIONS:					
1	_   1	1	4.6						BMW X5 4.6 is							
*	*	*	*						*							
*	*	*	*						*							
*	4	*	*						*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]				RAF = 0.94 RAF = *	NMOG or NMHC STD	r i ot nitroaer	1 HCHO=1	ormaiden	vde 2PM≂	<b>D</b> articulate	matter	RAFEresci	Hvity adius:	O≃carbon n tment factor	2/3 D [a/4a	
CERT STD		NMOG	NMHC	mg=milligr		t-soak KL	. [g/mi]=ru	inning loss =1 <b>00</b> 0 miles	ORVR [g	/galion	lispensed]=  hrenheit	on-board r	efueling vap	OF recovery	g=gram	
*	*   *		CERT [g/mi]	CERT [g/mi]	[g/mi]		g/mi]		Ox [g/mi]		CHO [r		PM [	g/mi]	Hwy NO	x [g/mi]
5-10-12 miles			ra1	131	1	CERT	STD	CER	TST	D CE	RT	STD	CERT	STD	CERT	STD
			0.118	*	* 0.160		4.4	0.1	0.4	4	2	18	*	*	0.003	0.8
		@ UL	0.134	*	0.230	1.4	6,4	0,2	0.6	6	4	27	*	*	0.01	1.2
	@ 50°F	F & 4K	0.176	*	0.320	2.5	4.4	0.1	0,4	4	2	36	*	*	*	*
CO [	°F&	LE	= @ 4K (SUL EV) or 50K (T	ier 1, TLEV)	NMHC+N (comp				NMHC+NOx [g/mi] [US06]		С	O [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	K	SFTP 2 = @ UL (T		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CEF	T STD	CER	T STD	CERT	STD
CERT	5.7			SFTP 1	*	*			* 7		*	*	*	*	*	+
STD	12.5		40.00	SFTP 2	* 4		•	*	•	*	*	*	*	*	*	*
@ UL	E۱	/APOR	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2 EVAPORATIVE FA							AILY 3	E	EVAPORATIVE FAMILY 4		
	3-D	2-0		ORVR	<b>3-</b> D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.6	1.9	0.02	0.04	*	*	*	*	*	*	*	*	*	*	*	
STD	2.0	2.5	0.05	0.20	*			*	*	*	*	*	<del> </del>	*	*	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 23 ED day of September 2002.

Allen Lyons, Chief

Mobile Source Operations Division