S. Hala



## **BAYERISCHE MOTOREN WERKE AG**

EXECUTIVE ORDER A-008-0147 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL TEST GROUP			M	VEHICLE TYPE C=passenger car; LDT=light-duty t DV=medium-duty vehicle; LVW=io vehicle weight; ALVW=adjusted LV	ruck; CATEG aded vehic	ST EMISSION STAND ORY {LEV=low emile; TLEV= transitional LE ltra LEV; SULEV=super L	ission V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	3 3BM	3BMXV01.6R50			PC		LEV		100K / 100K	Gasoline				
No.	EVAPOR FAMILY			No.	SPECIAL FEATU EMISSION CONTROL S		* = not applicabl	e OC	/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S				
1	3BMXR0	3BMXR0093R50			WU-TWC, TW	C, HO2S(2), SFI,	AF	S/HAFS=air-fuel ratio s	ensor/heated AFS_EGR=exhause					
2	*	*			WU-TWC, TWC, HO	2S(2), SFI, SC,	gas	gas recirculation AiR/PAIR=secondary air injection/pulse AIR MFI/SFI= multiport fuel injection/sequential MFI						
3	• 5			3			ТВ	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
4	* 125			4		+	dia							
EVAF No.	ECS No.													
1	1		1.6		BMW Mini Cooper									
1	2		1.6		BMW Mini Cooper S									
*	*	Т	*											
*	*	İ	*		•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]			RAF ≈ 0.94 RAF = *	NMOG or	or nitroge	in HUHO	≕tormaiden	yde PM≖ı	particu	riate matte	e RAF=rea	ctivity adius	O=carbon r	r 2/3 D (a/to	etiz7/3 day
CER	T	STD	NMOG NMHC		NMHC	mg=millig	ot•soak N  ram m :	(L[g/mi]≐ru =mile K=	nning toss :1000 miles	ORV	/R [g/gallo: ≔degrees	n dispensed Fahrenheit	]=on-board SETP=sur	refueling var	por recovery	g=gram
0.05	7	0.062	CERT [g/mi]	CERT [g/mi]	[g/mi]	CO [g/mi]		. NO	x [g/mi]		нсно	[mg/mi]		g/mi]	Hwy NOx [g/mi]	
				[9/431]		CERT	STD	CER	T ST	D	CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.053	*	0.075	0.7	3.4	0.1	0.2	2	1	15	•	*	0.02	0.3
3	· •	@UL	0.057	•	0.090	0.8	4.2	0.1	0.3	3	1	18	*	*	0.02	0.4
22.4	@ 50	°F & 4K	0.140	•	0.150	1.8	3.4	0.02	0.2	2	1	30	*	4	•	•
	CO [g/mi] @ 20°F &		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			ox [g/mi] osite)	CO [g/mi] (composite)		NMHC+N [g/mi] [US				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	K	SFTP 2	= @ UL (Tle	r 1, TLEV)	CERT	STD	CERT	STD	CERT	S	TD CE	RT ST			CERT	STD
CERT	1.9	4.5 a.k.		SFTP 1	•	*	•	*	•	,	•	+ +	*	•	*	*
STD	10.0		4 7	SFTP 2	*	*	•	•	*		•	• •	-	•	*	•
@ UL		EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPO					ATIVE FA	AMILY 3	T E	EVAPORATIVE FAMILY 4		
	3-D	2-[	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-0	RI	- ORV	R 3-D	2-D	RL	ORVR
CERT	1.7	0.8	0.01	0.13	*	•	*	•	*	*	*	•	•	*	*	*
STD	2.0	2.	0.05	0.20	•	•	*		•	*		*	•	*	•	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 23 day of September 2002.

Allen Lyons, Chief

Mobile Source Operations Division

Jeliste war GR