

DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0581
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| YE | MODEL YEAR TEST (| | | | M | VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW) | EXHAUST EMISSION STANDARI CATEGORY (LEV=low emissionelle); TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV | | | EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles) | FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas) | | | |
|-----------|----------------------|---------------------------|----------|--------------------|-----|--|---|---|--|---|---|--|--|--|
| 20 | | | XT02.43E | 00 | | LDT 3,751-5,750 pounds LVW | LEV | | | 100K / 100K Gasoline | | | | |
| No. | | /APORATIVE MILY (EVAF) | | | No. | SPECIAL FEATURES EMISSION CONTROL SYSTEI | & VIS (ECS) | * = not applicable | at. ADSTWC=adsorbing TWC | | | | | |
| 1 | 3CR | XR015 | 5GCH | | 1 | H02S(2), TWC (2 | | AF | -S/HAFS≂air-fuel ratio s | O2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust | | | | |
| 2 | | • | | | 2 | * | | ga | agas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo (support barrant) | | | | | |
| 3 | | * | | | 3 | * | | −Итв | | | | | | |
| 4 | | * | | | 4 | * | *************************************** | CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallet (2) suffix=series | | | | | | |
| EVA No | | ECS No. | | ENGINE SIZE (L) | | VEHICLE VEH MAKES & MODELS STA | HICLES SUB | 13 | ABBREVIATIONS: | | | | | |
| 1 | | 1 | | | | Jeep Liberty 2WD/4WD | | | | | | | | |
| * | _ | * | * | | | | * | | | | | | | |
| | _ | * * | | | * | | | | | | | | | |
| | <u>_</u> L | * | * | | | | | * | | 78. | | | | |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| A | NMOG FLEET AVERAGE [g/mi] | | | | RAF=0.94 RAF = * | NMOG or | | | | | | | | | arbon mono | | | |
|---------|------------------------------|------|---|----------------|---------------------|----------------------|------------|--------------------------|-------------------------|---------------------------|------------|--------------|-------------|-------------------------------|----------------------|---------------------|------------|--|
| С | CERT STD | | NMOG NMHC | | NMHC STD | mg=milligr | 1.204K KF | [g/mi]=run | ining loss 000 miles | UKVK | ∢ [g/ga⊪or | 1 dispensed] | =on-board i | refueling vap plemental fe | or recovery | g=gram | | |
| 0 | 0.095 | | 0.093 | CERT [g/mi] | CERT [g/mi] | [g/mi] | | g/mi] | | x [g/mi] | | нсно | | PM [| g/mi] | | x [g/mi] | |
| 2000000 | | | | [9,] | | | CERT | STD | CERT | STI |) | CERT | STD | CERT | STD | CERT | STD | |
| | | | @ 50K | 0.050 | * | 0.100 0.130 | 1.9 1.9 | 4.4 5.5 * | 0.2 | 0.4 | 1 | 1 | 18 | * | * | 0.03 | 0.5 0.7 | |
| . 52. | | | @ UL | 0.050 | | | | | 0.2 | 0.5 | , | 1 | 23 | * | | | | |
| | | | F & 4K | * | | | | | * | * | | * | • | * | * | * | * | |
| | 0 [g 20°l | | SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) | | | NMHC+NC (compo | | CO [g/mi] (composite) | | NMHC+NOx [g/mi] [US06] | | | | | HC+NOx | CO [g/mi] [SC03] | | |
| | 50K | | SFTP 2 | = @ UL (Tie | 1, TLEV) | CERT | STD | CERT | STD | CERT | STE | CE | | | | CERT | STD | |
| CEI | ₹Т | 7.3 | 14.6 | 12.5 | SFTP 1 | * | * | * | * | * | * | - | | | * | * | * | |
| ST | D | 12.5 | 10 | | SFTP 2 | * | * | * | * | * | * | | • | * | • | * | * | |
| @ (| ıı L | E, | VAPOR | ATIVE FAI | /ILY 1 | EVAPORATIVE FAMILY 2 | | | | EVAPORATIVE FAMILY 3 | | | | E | EVAPORATIVE FAMILY 4 | | | |
| | | 3-D | 2-0 | | ORVR | 3-D | 2-D | RL (| DRVR | 3-D | 2-D | RL | ORVI | | 2-D | RL | ORVR | |
| CEF | | 1.1 | 0.7 | 0.001 | 0.06 | * | * | * | * | * | * | * | * | * | • | * | * | |
| STE |) | 2.0 | 2.5 | 0.05 | 0.20 | * | * | * | * | * | * | * | | **** | * | + | * | |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models have been certified on the condition that the manufacturer provide all on-board diagnostic demonstration data required by 13 CCR Section 1968.1(g) by August 1, 2002. Failure to submit the required demonstration data by the specified date, or failure of the submitted demonstration data to show compliance with the test procedures, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 25th day of June 2002.

Aller Lyons, Chief

Mobile Source Operations Division