



Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty tr MDV=medium-duty vehicle; LVW=loa vehicle weight; ALVW=adjusted LV	ruck; C	ATEGORY vehicle: Ti	MISSION STANDA (LEV=low emis EV= transitional LEV EV; SULEV=super UL	sion	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
2003		3FEXV05.5C00			PC		TIER 1			100K / 100K	Gasoline (Indolene)				
No.		APORATIVE MILY (EVAF)		No	SPECIAL FEATU EMISSION CONTROL S					13 TO WATER OLD CAL. OLD/10023-027020 Sensor/hearen (125					
1	1 3FEXR0203C00				2TWC, 2HO2	2S(2), AIR,	SFI, OBD	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed							
2	*					*		AIR MFI/SFI= multiport fuel injection/sequential MFI							
3				3		*		TBI= throttle body injection TC/ŚC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
EVAF No.	1 -	CS lo.	ENGINE SIZE (L		VEHICLE MAKES & MODELS		ICLES SUBJECT TO SETP			ABBREVIATIONS:					
1		1 5.5			Ferrari: 456 MGTA, 456 MGT										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]				MOG @	RAF= * 4F = *	NMOG or	Inttrogen	HUHUSTO	rmaidenvd	e PM:	particul	ate matte	er RAF=	reactivit	v adluetmar	at factor	xide NOx= 2/3 D [g/test	1-2/2 day
CER				10G	NMHC	NMHC	diurnal+h mg=millig	ot-soak R	(L [g/mi]=ru	ınning I 1000 m	oss OF	₹VR [g/ga	illon disp es Fahren	ensed]=c	on-board ret	lueling vap	or recovery derail test pr	g=gram
0.09	9	0.062	CERT [g/mi]		CERT [g/mi]	[g/mi]		[g/mi]		Οx [g/ι			IO [mg/r	ni]	PM [g/	g/mi]	Hwy NO	x [g/mi]
		@ 50K			[9]		CERT	STD	CER	1	STD	CER	T S	TD	CERT	STD	CERT	STD
e april 100	equipment of the state of		* 0.10		0.25	0.8	3.4	0.4		0.4		*		*	*	0.04	0.5	
117.4	1975年11年			*	0.13	0.31	1.1	4.2	0.4		0.6			*	*	*	0.04	0.8
	@ 50			*	*	*	*	*	*		*	*		*	*	*	*	*
@ 20		L	LEV) or 50K (Tier 1, TLEV)			NMHC+NO (comp		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]					C+NOx [SC03]	CO [g/mi] [SC03]		
50K		SFTP 2 = @ UL (Tier		JL (Tier 1	I, TLEV)	CERT	STD	CERT	STD	CEF	₹T   5	STD	CERT	STD	CERT	STD	CERT	STD
CERT	8.6	120	W.O.	4	SFTP 1	*	*	•	*	*	T.,	*	*	*	*	*	•	*
STD	10.0		edd ar s 10 gin		SFTP 2	*	*	*	*	•		*	*	*	*	*	*	*
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				Y 3	EVAPORATIVE FAMILY 4				
	3-D	2-1	<b>D</b>	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2	-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.4	1.	3	0.04	0.06	*	•	*	*	*		•	*	*	*	*	*	*
STD	2.0	2.	5	0.05	0.20	*	*	*	*	*		*	*	*	*	*	*	*

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are conditionally certified pursuant to 13 CCR Section 1968.1(m)(6.2) (Malfunction and Diagnostic System Requirements-1994 and Subsequent Model-Year PC, LDT and MDV) because the on-board diagnostic II system of the listed vehicle models has been determined to have four deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50.00) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the vehicle manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California under this conditional certification, and pay the full fine owed for that quarter pursuant to this conditional certification; payment shall be made to the State Treasurer for deposit in the Air Pollution Control Fund no later than the thirty days after the end of each calendar quarter during the 2003 model year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5,000 per vehicle pursuant to Health and Safety Code 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this  $21^{57}$  day of November 2002.

Allen Lyons, Chief

Mobile Source Operations Division