

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD					VEHICLE TYPE PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	STAND (LEV=low e transitional	NUST EMISSION ARD CATEGORY mission vehicle; TLEV- I LEV; ULEV=ultra LEV EV=super ULEV)	-	EXHAUST (EXH) / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	3	3HNXV03.0HB4			PC		EV II ULEV		120K: EXH/ORVR 150K: EVAF Gasoline						
No.		PORA		No.	SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	Hw	OC/TWC=oxldizing/3-way cat. ADSTWC=adsort						
1	3HNXR0140BBA			1	2HO2S, TWC, 2WUTWC,	SFI, EGR, 2AF	_  ^	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFi= multiport fuel injection/sequential MFI/SFi= multiport fuel injection of the control of the							
2	•			2		•	ľΙĀ								
3	•			3		•	HC								
4		*					diagnostic prefix 2=parallel (2) suffix=series								
EVA No.		ECS No.	ENGINE SIZE (L)				ECT TO SFTP	ABE	BREVIATIONS:						
1	1 3.0				Honda Accord (LX/EX Sedan, LX/EX Coupe)										
*	_	•	*		•										
*				$\neg$	•										
*		<del>  •   •   •   •   •   •   •   •   •   •</del>			•										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF=0.94 CH4 RAF = *		NMOG or		HCHO-for	=non-CH4 maldehyde - [g/mi]=rui	DMmna	etien de	te matter	RAFERAN	tivity a idi≖on	djustmen board refi	t factor 2 Leiing vap	or recovery	g=gram		
CERT	Г	STD	NMO		NMHC CERT [g/ml]	NMHC STD [g/mi]	mg=milligram mi=mile K=1000 miles CO [g/mi] NOx [g/mi]					-degrees	Fahrenheit [mg/mi]	SF	TP=supplemental fed PM [g/ml]		deral test procedure Hwy NOx [g/ml]	
0.046	3   (	0.062	CER				CERT	STD	CERT			CERT	STD	<del>  c</del>	ERT	STD	CERT	STD
	900	@ 50K	0.033	3	. *	0.040	0.4	1.7	0.03	0.0	5	0.2	8		•	•	0.03	0.07
		@ UL	0.037	,  -	*	0.055	0.5	2.1	0.05	0.0	7	0.3	11		*	*	0.04	0.09
10.04	<i>ര</i> 50	°F & 4K			*	•	•	•	*	*		*	*		*	•	*	•
CO [	g/mi]	SETP	1 = @ 4K (SUL LEV) or 50K (T		ULEV,	NMHC+NOx [g/mi				NMHC+NO: [g/mi] [US06					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
@ 20°F & 50K		SFTP	2 = @ UL	(Tier 1, 1	1, TLEV)	CERT	STD	CERT	STD	CERT	S	TD C	ERT :	STD	CERT	STD	CERT	STD
CERT	1.8	379.5			SFTP 1	*		•	*	0.07	0	.14	0.1	8.0	0.02	0.20	0.1	2.7
STD	10.0				SFTP 2	*	*		*	*		•	*	*	•	*	*	•
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2 EVAPOR				RATIVE F	AMILY 3		EVAPORATIVE FAMILY 4					
	3-D			RL	ORVR	3-D	2-D	RL.	ORVR	3-D	2.	D F	RL OI	RVR	3-D	2-D	RL	ORVR
CERT	0.16	0.3	26 0	.005	0.01	•	*	*	•	*			*	*	•	<u> </u>	<del>                                     </del>	<del>                                     </del>
STD	0.50	) 0,	85 C	0.05	0.20	*	*	*	•	*		•	*	*	*			

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 3000 day of August 2002.

Allen Lyons, Chief

Mobile Source Operations Division