## HONDA MOTOR CO., LTD.

EXECUTIVE ORDER A-023-0344 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR		TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=light truck; MDV=medium-duty veh LVW=loaded vehicle weigh ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; SULEV=ultra LEV; SULEV=super ULEV)			EXHAUST (EXH) / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	_	3HNXV01.0PCE			Ц,	PÇ	LEV II SULEV			120K: EXH/ORVR 100K: EVAF	Gasoline plus Battery- Assist				
No.		FAMILY (EVAF)				SPECIAL FEAT EMISSION CONTROL	TURES ( SYSTEM	& MS (ECS)	* = not applicable	0,0	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbin				
1	3HN2	3HNXR0083AAA			i	TWC, WUTWC,				WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFi= multiport fuel injection/sequential MFI TBI=					
2		*			2		*		g						
3		*			3		*		∦т						
4		*		4	1		*			AC=charge air cooler OBD ( lagnostic prefix 2=parallel	F) / (P)≂full /partial on-board				
EVAI No.		ECS No.	ENGIN SIZE (			VEHICLE MAKES & MODELS	VEF	IICLES SUBJ	ECT TO SFTP E UNDERLINED	ABE	BREVIATIONS:				
1		1	1.0			Honda Insight (CVT Transmission)									
*		* *				*									
*	* *														
*		* *							*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.) Since no NMOG RAF is adopted by the Air Resources Board for passenger car SULEVs, the manufacturer has agreed to a default value listed below.

NMOG FLEET AVERAGE [g/mi]				) RAF=1.00 RAF = *	NMOG or								rbon CO=c				
CERT STD		NMOG NMHC		NMHC	mg=millig	ot-soak K	⊏ լց/ռույ-ռ	ınning loss 1000 miles	ORVR	g/gailon	dispensed] hrenheit	on-board resupt	efueling var	or recovery	q=qram		
0.04	6 (	0.062	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		Ox [g/mi]	F	і оно	mg/mi]	PM [c	g/mi]		x [g/mi]	
			[a,,,,,]	[9/111]		CERT	STD	CER	T   ST	DC	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	*	*	*	*	*	*	•		*	*	*	*	*	*	
7,00	ii in	@ UL	0.004	*	0.010	0.01	1.0	0.01	0.0	2 0	0.04	4	*	*	0.004	0.03	
	@ 50°F		*	*	*	*	*	*	*		*	*	*	*		*	
@ 20		贈 LE	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			(composite) (c			D [g/mi] NMHC+N mposite) [g/mi] [US					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	K	SFTP 2 = @ UL (Tier		er 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT STI	CERT	STD	CERT	STD	
CERT	0.2	147		SFTP 1	*	*	*	*	0.01	0.14	3.	3 8.0	0.05	0.20	0.01	2.7	
STD	10.0	1.42		SFTP 2	*	*	*	•	*	*	•		*		*		
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR					PORATI	VE FA	MILY 3	E	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR	
CERT	1.4	1.3	0.0	0.06	*	•	*	*	*	*	*	*	*	*	*	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	*	•	+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_ day of September 2002.

Allen Lyons, Chief Mobile Source Operations Division