

HYUNDAI MOTOR COMPANY

EXECUTIVE ORDER A-254-0092
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	STANDA (LEV=low en transitional	JST EMISSION RD CATEGORY Ilssion vehicle; TLEV= LEV; ULEV=ultra LEV; V=super ULEV)	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	_	3HYXV02.0XOC		C	PC	LE	V II SULEV	120K: EXH/ORVR 150K: EVAF	Gasoline (Indolene)				
No.		APORA VILY (E		No.	SPECIAL FEATURE EMISSION CONTROL SYS		* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing T					
1	ЗНУ	3HYXR0148PAX			HO2S(2), WUTW	C, TWC, SFI, OB	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board						
2		* 2				* .							
3	.J	* 3				*							
4		*		4		*	diagnostic prefix 2=para	JBD (r) / (r)=ruii /partial on-board illei (2) suffix=series					
EVAI No.		ECS No.	ENGIN SIZE (I		VEHICLE NAKES & MODELS S	ÆHICLES SUBJ	ECT TO SFTP E UNDERLINED	ABBREVIATIONS:					
1		1 2.0			Hyundal Elantra								
*		*	*		•								
*.													
*		* *					+						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ R AVERAGE [g/mi] CH4 RAF				NMOG or	Introgen	HUHUTO	rmaidenyde	e PM≃bari	iculate ma	itter R	AFarea ctivi	on CO≖ca ty adjustme	nt factor 1	7/2 D [m/taet	1-2/2 day	
CER	RT STD		NMOG	NMHC	NMHC	mg=millig	7 ABOSTIC	r [8/ամ≖ւռ։	nning loss 1000 miles	ORVR [g/	gallon c	(Ispensed)	on-board re SFTP=supp	fueling vap	or recovery	g=gram
0.05	2 (0.062	CERT	,	[g/mi]		[g/mi]		Ox [g/mi]		CHO [m		PM [g		Hwy NO	
2007 - 2047 - 204 A	a development and 8		[g/mi]			CERT	STD	CER	STC	CE	RT	STD	CERT	STD	CERT	STD
		@ 50K	*	•	•	•	•	*	•	,	•	•	•	*	*	
		@ UL	0.006	*	0.010	0.1	1.0	0.01	0.02	2 0.	.3	4	*	*	0.002	0.03
	@ 50	°F & 4K	0.014	*	0.020	0.3	1.0	0.002	2 0.02	2 0.	2	8	*	•	*	
@ 20	CO [g/mi] @ 20°F &		LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/mi] (composite) (composite					0 [g/mi] [US06]		IC+NOx		[g/mi] 203]	
50K		SFTP 2 = @ UL (Tier 1, TLEV)		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	T STD	CERT	STD	CERT	STD
CERT	2.2			SFTP 1	•	*	•	•	0.01	0.14	2.7	8.0	0.002	0.20	0.4	2.7
STD	10.0			SFTP 2	*	*	•	*	*	*	*		•	+		•
@ UL	EVAPORATIVE FAMILY 1				EVA	EVAPORATIVE FAMILY 2 EVAPORATIVE			PORATIV	ORATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
	3-D	2-D	³ RL	ORVR	3-D	2-D	RL.	ORVR	3-D	2-D	RL	ORVR		2-D	RL	ORVR
CERT	0.23	0.24	0.03	0.02	*	*	*	•	*	•	*	*	•	•	*	*
STD	0.50	0.65	0.05	0.20	*	•	•	*	•	•	*	-		+	+	-

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

14/74 day of January 2003.

Aller Lyons, Chief

Mobile Source Operations Division