

## MAZDA MOTOR CORPORATION

EXECUTIVE ORDER A-016-0279 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD	R.	TEST GROUP		M	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded rehicle weight; ALVW=adjusted LVW)	CATEGOR vehicle;	EMISSION STAND Y (LEV=low emi TLEV= transitional LE LEV; SULEV=super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200		3TKXV03.0CLM				PC		LEV		100K / 100K	Gasoline		
No.		PORATIVE ILY (EVAF)			No.	SPECIAL FEATURES EMISSION CONTROL SYSTE	& MS (ECS)	* = not applicable	e   OC	C/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC		
1	3TK)	XR0150PPC			1	2WU-TWC, 2TWC, 2HO2		MAL	'O/⊓AFO≖air-fuel ratio s	O2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust			
2		*			2		, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ga	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*			3	•		ТВ	I= throttle body injection	n TC/SC=turbo /super charges			
4		*			4	•	,		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVAI No.		ECS ENGINE No. SIZE (L)			VEHICLE VE MAKES & MODELS STA	HICLES SUBJECT TO SFTP NDARDS ARE UNDERLINED			ABBREVIATIONS:				
1		1 3.0						Mazda 6					
*		*	*					*					
*		*	*					*	-				
*		•	*					*					

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET AVERAGE [g/mi]			RAF=0.94 RAF = *	NMOG or							n-CH4 hydro r RAF=reac					
CER	Τ	STD	NMOG	NMHC	NMHC STD [g/mi]	diurnal+ho mg=milligi	or oour it	- [Avviil]-u	nning loss 1000 mile	OKV	rt (g/galioi	n dispensed] Fahrenheit	=on-board :	refueling var	or recovery	q=qram	
0.05	1   1	0.062	CERT [g/mi]	CERT [g/mi]		CO [g/mi]			Ox [g/mi]	[g/mi] H		HCHO [mg/mi]		g/mi]	Hwy NO		
			<u></u>			CERI	STD	CERT	ST	D	CERT	STD	CERT	STD	CERT	STD	
進費		@ 50K	0.025	*	0.075	8.0	3.4	0.1	0.	2	0.3	15	*	*	0.02	0.3	
100		@ UL	0.031	*	0.090	1.2	4.2	0.1	0.	3	0.4	18	*	*	0.04	0.4	
	@ 50	°F & 4K	F & 4K *		*	*	*	*	•		*	*	*	*	*	*	
@ 20		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)					(composite)		NMHC+NC [g/mi] [US0				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
<del></del>	50K		SFTP 2 = @ UL (Tier		CERT	STD	CERT	STD	CERT	ST	D CE	RT ST	CER	T STD	CERT	STD	
CERT	2.0			SFTP 1	*	*	*	*	0.08	0.1	4 2	.0 8.0	0.02	0.20	0.3	2.7	
STD	10.0			SFTP 2	*	*	*	*	*	*			*	*	*	+	
@ UL		VAPOR	ATIVE FAN	AILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				F	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D				2-D	RL	ORVR	
CERT	0.9	1.0	0.001	0.03	*	*	•	*	*		<del>-   ```</del>	*	*	*	*	ORVK	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	+	+	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of September 2002.

Allen Lyons, Chief

Mobile Source Operations Division