

FUJI HEAVY INDUSTRIES, LTD.

EXECUTIVE ORDER A-002-0118 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP		Р	VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			CATEGOR vehicle: 1	EMISSION STAND Y (LEV=low emi LEV= transitional LE LEV; SULEV=super U	ssion	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)		
200	3 :	3FJXV02.0LGL			PC				LEV		100K / 100K	Gasoline		
No.		EVAPORATIVE FAMILY (EVAF)		No	Io. SPECIAL FEATURES EMISSION CONTROL SYSTE		& VIS (ECS)	* = not applicable	0	DC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TW VU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2				
1	3FJXI	JXR01251BD				TWC(2), HO2:			LIAI	FS/HAFS≃air-fuel ratio s	ensor/heated AFS_EGR=exhaust			
2		*				*					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI			
3		* **				***			TE	TBI= throttle body injection TC/SC=turbo /super charger				
4		· Oliver		4		· · · · · · · · · · · · · · · · · · ·	•		ăí	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVĀF No.				VEHICLE KES & MODELS	VEHICLES SUBJECT TO SFTP STANDARDS ARE UNDERLINED				ABBREVIATIONS:					
1	1	1	2.0		SUBARU: IMPREZA WRX, IMPREZA WAGON									
	•	•	*											
•		* *			•									
*		*	•						*		70			

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET N AVERAGE [g/mi]			NMOG @ RAF=0.94 CH4 RAF = *		TOT THUROGE	п нсно	Tormaldeh	/de PM=/	arficula	ite matter	RAFEresci	carbons Civity adjustn	ant factor	2/3 D Indoor	the District
CER	RT STD		NMOG	NMHC	NMHC STD [g/mi]	mg=millig	DI-SOAK H	և լց/ույյ=ռ	inning los: 1000 miles	s ORV	R [g/galloi	n dispensed ahrenheit]≖on-board r	efueling var	or recovery derail test pr	a=aram
0.07	5	0.062	CERT CERT [g/mi] [g/mi]				[g/mi]		Ox [g/mi]		HCHO	[mg/mi]	PM [Hwy NO	
			[Auni]	[8,111]	1	CERT	STD	CER	T ST	D	CERT	STD	CERT	STD	CERT	STD
	@ 50K		0.040		0.075	0.7	3.4	0.1	0.	2	1	15	•	•	0.01	0.3
72.6.4	á- i	@ UL	0.042	*	0.090	8.0	4.2	0.1	0.	0.3		18	*	+	0.01	0.4
**************************************	@ 50	°F & 4K	0.073	•	0.150	1.1	3.4	0.1	0.	2	1	30	*	•	*	•
CO [@ 20	g/mi} °F &	[] 티	= @ 4K (SUL EV) or 50K (T	ier 1, TLEV) [NMHC+NO (comp			[g/mi] posite)		C+NOX		CO [g/mi] [US06]		HC+NOx		[g/mi] 2031
50	50K		SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	ST	D CE	RT ST			CERT	STD
CERT	4.1			SFTP 1	•	*	•	•	*	•			*	*	•	
STD	10.0			SFTP 2	*	•	*	*	*	•	 	. .	•	*	•	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR					PORA	ATIVE FAMILY 3 EVAPORATIVE FAMILY 4					
_	3-D	2-[RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR
CERT	0.7	3.0	0.001	0.02	*	•		*	*	•	*	*.	•	+	•	•
STD	2.0	2.5	0.05	0.20	•	•	*	*	*	•	*	*		*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 4th day of June 2002.

Allen Lyons, Chief

Mobile Source Operations Division