Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-duty truck; MDV=meditum-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EI STANDARD C (LEV=low emiss TLEV= transiti ULEV=ultra SULEV=supe	ATEGORY lon vehicle; onal LEV; LEV;	USEF	(HAUST & ORVR / EVAPORATIVE UL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	005 5BMXV04.4LE\			V	PC	LEV			OK / 150K (EVAF 1) OK / 100K (EVAF 2)	Gasoline				
No.		APORATIVE MILY (EVAF)			SPECIAL FEATU EMISSION CONTROL S		* = not app	licable	OC/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S				
1	5 B M	5BMXR0090E60			2TWC, 2HAFS,	2H02S, SFI, AIR, (MAFS/HAFS=air-fuel ratio s	ensor/heated AFS_EGR=exhaust						
2	5BM	BMXR0158E65				4	AIR MFVSFI= multipor	IResecondary air injection/pulsed truel injection/sequential MFI						
3		*				on TC/SC=turbo /super charger OBD (F) / (P)=full /partial on-board								
4		*		4		*			diagnostic prefix 2≖para	illel (2) suffix=series				
EVAI No.		CS No.	ENGINI SIZE (L		VEHICLE MAKES & MODELS	VEHICLES SUB- STANDARDS AF			BBREVIATIONS:					
1		1 4.4		1	BMW: 5451, 645Cl, 645Cl Convertible									
2		1 4.4			BMW: 7451, 745LI									
*		* ,*												
*		* *								-				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF = * CH4 RAF = *		NMOG or											
CERT	STD	NMOG	NMHC	STD [g/mi]	mg≖milli	gram mi=	mile K≖	1000 mile	s F≖d	egrees F	ahrenheit	SFTP=sug	plemental fe	ederal test p	rocedure
0.053	0.049	CERT [g/mi]	CERT [g/mi]			[g/mi]		Ox [g/mi]			mg/mi]		g/mi]	Hwy NO	
Petr			ranini		CERT	STD	CERT	r si	D C	ERT	STD	CERT	STD	CERT	STD
	@ 50K	0.037	*	0.075	0.5	3.4	0.1	0.	.2	1	15	*	*	0.01	0.3
1.5	@ UL	0.043	•	0.090	0.6	4.2	0.1	0	.3	1	18	*	*	0.01	0.4
· @	50°F & 4K	0.042	•	0.150	0.7	3.4	0.1	0	.2	1	30	*	*	ŵ	*
CO [g/m @ 20°F 8		= @ 4K (SUL EV) or 50K (T		NMHC+N (comp			g/mi] posite)		IC+NOx] [US06]	(CO [g/mi] [US06]		HC+NOx ni] [SC03]		(g/mi] C03]
50K	SFTP 2	: = @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD
CERT 2.	.9	**	SFTP 1	*	*	*	*	0.11	0.14	0.	5 8.6	0.1	0.20	0.2	2.7
STD 10	.0		SFTP 2	•	*	*	*	*	*	,	*	*	*	*	*
@ UL	EVAPOR	VAPORATIVE FAMILY 1			EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D 2-I	D RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	. ORV	R 3-D	2-D	RL	ORVR
CERT 0	0.3	0.02	0.12	0.6	0.5	0.03	0.04	*	*	*	*	*	*	*	•
STD 0	0.50 0.6	0.05	0.20	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1214

day of October 2004.

Allen Lons, Chief

Mobile Source Operations Division