GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1209-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP VEHICLE TYPE		EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		(*=N/A (RMEDIATE N-USE PLIANCE or full in-use; exh. / evap. diate in-use)	FUEL TYPE	
2005	5GMXT02.8189	LDT: 3751-5750 Pounds LVW	USEPA Bin 9a (opt)	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2	
			Counted as ARB ULÉV	100K	100K	٠	*	Unleaded)	
No.		SPECIAL FEATURES	EVAPORATIVE	FAMILY (EV	AF)		DISPLAC	EMENT (L)	
1	WU-TWC,TV	VC, HO2S(2), SFI, OBD(F)	5GMXR0			DIOFEAC	EMENT (L)		
*		*							
•		*	-			2.8			
*		*							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1209 dated April 5, 2004.

Executed at El Monte, California on this 29th day of November 2004.

Allen Lyons, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing

		NMOG or	CH4=meth HCHO=for	ane; NMOG	=non-CH4	organic gas	; NMHC=n	on-CH4 hyd	rocarbon;	CO=carbon	monoxide; I	ne test fue	of nitrogen:		
CERT	STD	NMOG CERT	NMHC	NMHC STD	hot-soak; F mi=mile; K	RL (g/mi)=ru =1000 mile:	nning loss; s: F=dearee	ORVR [g/g	allon dispe	nsed]=on-b	pard refuel	ing vapor reast est procedure	covery; g=g	diurnal+ ram; mg=milli	gram
0.060	0.076	[g/mi]	CERT [g/mi]	[g/mi]	CERT	[g/mi] STD	CERT	x [g/mi]	н	CHO [mg/	mi]	PM [g		Hwy NO	Ox [g/mi]
4.164	@ 50K	0.065	*	0.100	0.8						TD	CERT	STD	CERT	STD
11.00	@ UL	0.069	*	0.130		3.4	0.1	0.2		*	15.	*	*	0.03	0.27
A PARTY	@ 50°F & 4K			0.130	0.9	4.2	0.2	0.3		<u>*</u>	18.	*	*	0.09	0.40
The second second	@ 30 T & 4K				*	*	*			•	*	*	*	*	*
) [g/mi] °F & 50K			NMHC+NO (compo	osite)	CO [comp		NMHC [g/mi]			[g/mi] 506]		C+NOx [SC03]	CO [SC	[g/mi] :03]
CERT		a sur training	C C A	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
	5.7	SFTP @ 40		*	*	*	. •	0.08	0.25	0.4	10.5	0.03	0.27	0.2	3.5
STD	12.5	SFTP (0 100000 miles	0.30	1.04	*	*	*	*	2.8	14.6		•	1.6	4.9

Evaporative Family	3-Days Diurnal + Hot Soak (grams/test) @ UL			est) @ UL	Runnin (grams/m		On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
5GMXR0175922	0.5	2.0	0.8	2.5	0.00	0.05	0.14		
	*	*	*	*	*	*	0.14	0.20	
•	*	*	*	*	*	*			
*	+	*	*	*		•			

* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2005 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP]	
CHEVROLET	COLORADO 2WD	5GMXR0175922	1	2.8	•	•	SFTP	Full
CHEVROLET	COLORADO 4WD	5GMXR0175922	1	2.8	*	*	SFTP	Full
CHEVROLET	COLORADO CREW CAB 2WD	5GMXR0175922	1	2.8	*	•	SFTP	Full
CHEVROLET	COLORADO CREW CAB 4WD	5GMXR0175922	1	2.8	*	*	SFTP	Full
GMC	CANYON 4WD	5GMXR0175922	1	2.8	*	*	SFTP	Full
GMC	CANYON CREW CAB 4WD	5GMXR0175922	1	2.8	*		SFTP	Full
GMC	CANYON 2WD	5GMXR0175922	1	2.8	*	*	SFTP	Full
GMC	CANYON CREW CAB 2WD	5GMXR0175922	1	2.8	*	•	SFTP	Full
CHEVROLET	COLORADO CAB CHASSIS INCOMPLETE 2WD	5GMXR0175922	1	2.8	*	*	SFTP	Full
GMC	CANYON CAB CHASSIS INCOMPLETE 2WD	5GMXR0175922	1	2.8	*	*	SFTP	Full