Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL YEAR TEST GROUP			JP	VEHICLE TYPE (PC≖passenger car; LDT≖light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			STANI (LEV≃low transition	AUST EMISSION DARD CATEGORY emission vehicle; TLE al LEV; ULEV=ultra LE LEV=super ULEV)	V=	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG≃compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
2005 5NSXT05.6P9A						MDV: 5751 - 8500 Pounds ALVW 1) USEPA Non-Tier 2 Bin 8 2) Counted as ARB LEV I S				LEV	120K / 150K	Gasoline			
No.	EVAF FAMI	LY (E	VAF)	١	o.	SPECIAL FEAT EMISSION CONTROL			Q.	C/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC				
1	5NSXR0174PBA				1	2TWC(2), 2H	IAFS, 2H	02S, SFI, OB	MAF	WU= warm-up cat. 02S/H02S=oxygen sensor/heated 02S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MF/SFI= multiport fuel injection/sequential MFI					
2		•			2		*		ga Al						
3		•			3	*					"Not the throught of the second TC/SC=turbo /super charger				
4		*			4	*				di	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVAI No.		CS lo.	ENGIN SIZE (1		VEHICLE MAKES & MODELS	CLES SUBJECT TO SFTP DARDS ARE UNDERLINED ABE			BREVIATIONS:					
1		1	5.6		Nissan: Armada 2WD, Armada 4WD, Titan 4WD										
1		1 5.6				Infiniti: QX56 2WD, QX56 4WD									
		*	*		A										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ CH4 R) RAF = * AF = *	NMOG or	Of nitroger	1 HCHO±	formaldehv	de PM≃n	articula	ita matte	r RAF±reac	carbons Co	mant factor	2/3 D [a/to	e+1=2/2 day	
CER	T STD		NMOG	NMHC	NMHC STD	mg≖millige	it-soak Ki	_ [g/mi]=run	nning loss	ORVR	[g/gailor	i dispensed) Fahrenheit	≖on-board re	fueling vap	or recovery	g=gram	
		•	CERT	CERT	[g/mi]	CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
			[g/mi]	[g/mi]		CERT	STD	CERT	STE) (CERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.045	*	0.125	1.0	3.4	0.03	0.14	١	*	15	*	*	0.02	0.19	
		@ UL 0.048		*	0.156	1.1	4.2	0.04	0.20	,	*	18	•	*	0.03	0.27	
增度	@ 50°F	& 4K	*	•	*	*	*	•	•		*	*	•	*	*	*	
CO [@ 20	°F&	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)						CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	K	SFTP 2 = @ UL (Tier		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST			CERT	STD	
CERT	5.7		SF	TP @ 50K	0.06	1.49	*	*	*	*	1.	.4 13.2	2 *	*	1.3	4.4	
STD	12.5		SFTP @ 120K		0.07	2.09	*	*	*	*	1.	.4 19.:	3 *	*	1.4	6.4	
@ UL	EV	APORA	TIVE FAN	IILY 1	EVAPORATIVE FAMILY 2			2	EVAPORATIVE FAMILY 3				EV	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	. ORVI	₹ 3-D	2-D	RL	ORVR	
CERT	0.39	0.33	0.001	0.05	•	*	*	*	•	*	•		*	 •	+ •	*	
STD	0.90	1.15	0.05	0.20	•	•	*	•	*	*	*	•	•	*	+	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of September 2004.

Allen Lyons, Chief Mobile Source Operations Division