

TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0519 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP			M	VEHICLE TYPE C=passenger car; LDT=light-di DV=medium-duty vehicle; LVW vehicle weight; ALVW=adjuste	/=loaded d LVW)	STAN (LEV=low transition	AUST EMISSION DARD CATEGOR emission vehicle; TL al LEV; ULEV=ultra L LEV=super ULEV)	EV=	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)		
200		5TYXT04.7PKW			0	LDT: 6001-8500# GVV ver 3750# LVW, 5751-8500			LEV II ULEV		120K / 150K	Gasoline		
No.		APORATIVE MILY (EVAF)			No.	SPECIAL FEA EMISSION CONTROL	TURES &	S (ECS)	000	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O25				
1	5TYXR0190P30				1	2WU-TWC, 2TWC,			AF	S/HAFS=air-fuel ratio s	O2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust			
2		•					*		ga	— gas recirculation AlR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI ▼BI= throttle body injection TC/SC=turbo /super charger				
3		•					. *		ТВ					
4		*			4		*		dia	CAC=charge air cooler OBD (F)-/ (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVAF No.					ICLES SUBJECT TO SFTP			BBREVIATIONS:						
1	1		4.7		Toyota: Tundra (2WD and 4WD), Seguoia (2WD and 4WD)									
*			•											
*		* *							*		***			

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF = * CH4 RAF = *			NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal-hot-soak RL [g/mn]=running loss ORNR [g/gallon dispensed]=on-board refueling vapor recovery g=grammsmill[gram particle]												
CER	RT STD		NMOG		NMHC	NMHC	diurnai+ho mg=millig	oracak M	- [Ֆուտ]–ւո	nning los 1000 mile	SUR	vik įg/gailo	n dispensed] Fahrenheit	≃on-board :	refueling vap	OF recovery	g≖gram		
0.05	0	0.076	CERT [g/mi]		CERT [g/mi]	[g/mi]	CO	CO [g/mi]		Ox (g/mi			[mg/mi]		g/mi]	ederal test procedure Hwy NOx [g/mi]			
2 S. S. SARK I	@ 50K				[8,,,,,]		CERT	STD	CERT	Γ \$	LD	CERT	STD	CERT	STD	CERT	STD		
			0.03	0.030	*	0.040	0.3	1.7	0.02	0.	05	*	8	*	•	0.01	0.07		
77	1/ 0 @		0.03	5	*	0.055	0.3	2.1	0.03	0.	07	*	11	*	*	0.01	0.09		
6. 1. 1 .	@ 50	°F & 4K +			*	*	*	*	•		•	*	•	*	*	*	*		
CO [@ 20	°F&	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV			r 1, TLEV)	NMHC+NOx [g/mi] (composite) (CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]			
50	50K		= @ UL	(Tier 1	, TLEV)	CERT	STD	CERT	STD	CERT			RT ST			CERT	STD		
CERT	2.1	111		A ar	SFTP 1	*	*	*	. •	0.01	0.	60 3	.5 11.	8 0.03		0.4	4.0		
STD	12.5			20.7	SFTP 2	•	*	*	*		+-	•	* *		*	+	*		
@ UL	E	VAPOR	ATIVE	FAMIL	LY 1	EVAPORATIVE FAMILY 2			EV	APOR	ATIVE FA	AMILY 3		EVAPORATIVE FAMILY 4					
	3-D	2-1)	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-[2-D	RL	ORVR		
CERT	0.33	0.3	0 0.	.004	0.03	*	•		•				- OKVI	\ <u>3-0</u>	2-0	KL.	URVR		
STD	0.90	1.1	5 0	.05	0.20	*	*		•	*	*	*	*	- -	+	 	•		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

day of August 2004.

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____

Men Lyons, Chief

Mobile Source Operations Division

In be been for