BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0191 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for

MOD	EL			.] ,	VEHICLE TYPE PC=passenger car; LDT=light-duty truck;	STANDAR	ST EMISSION RD CATEGORY	ι	JSEFUL LIF	FUEL TYPE							
YEAR		TEST GROUP			WDV=medium-duty vehicle: LVW=loaded	TLEV= tr	EVAF 1		EVAF 2		(CNG/LNG≃compress ed/ liquefied natural						
					vehicle weight; ALVW=adjusted LVW)	ULEV SULEV	/=ultra LEV; =super ULEV)	EXH	EVAP/	EXH/	EVAP	gas; LPG=liquefied petroleum gas)					
2006		6BMXB03.0UL2		2	PC and LDT ≤ 6,000 pounds GVW PC; LDT 3,751-5,750 pounds LVW)	LEV	/ II ULEV		ORVR	ORVR	EVAP	Gasoline					
	EVAR		PORATIVE M		<u> </u>			120K	100K	120K	150K						
No.		MILY (EVAF)			SPECIAL FEATURES EMISSION CONTROL SYSTE	& MS (ECS)	* = not applica	able w	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S								
1	1 6BMXR013		36E46	1	2TWC, 2HAFS, 2HO	S, SFI, AIR, OBD (F)			O/DAPS=air-	IUBI FATIO SA	neor/heated	AFS ECD-outsund					
2	6BM	XR012	28E85	2		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			MFI/SFI= multinort fuel injection/sequential MFI TRI-								
3		*		3		*				cooler OBD (F) / (P)=full /partial on-hoard diagnostic profit							
EVA	FE	CS ENGINE			VEHICLE VE	HICI EÉ CHE	IECT TO CETE		parallel (2)	suffix=serie	\$						
No.		No. SIZE (L)				EHICLES SUBJECT TO SFTP ANDARDS ARE UNDERLINED											
1_		1	2.5		BMW: (PC) 325Cl, 325Cl Convertible												
1		1 3.0			BMW: (PC) 330Cl, 330Cl Convertible, 330Cl Convertible (Sport Package)												
2		1 3.0			BMW: (LDT 3,751 - 5,750 pounds LVW) X3 3.0i												
*				\top	2010 (1201 3,131 - 3,130 pounds LVW) X3 3.01												
•		*	•	+													

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NN AVE	NOG F	LEET [g/mi]) RAF = * RAF = *	NMOG or	CH4≃meti of nitroge	name NMO n HCHO:	G=non-CH4	organic g	ases NA	MHC≃non-	CH4 hydro	carbons C	g on gas O=carbon n tment factor	nonoxide N	Ox=oxide:
PC/L	DT1	LDT2	NMOG CERT	NMHC CERT	NMHC STD	mg=millig	ram mi:		nning loss 1000 miles	ONTR	[g/gallon o legrees Fa	ıspensedi	=on-board i	tment factor efueling vap plemental fe	Or recovery	g=gram
0.04	46	0.062	[g/mi]		[g/mi]	CERT	[g/mi] STD		x [g/mi]	1	НСНО [п	ng/mi]	PM [g/mi]	Hwy NO	
		A FOV	0.000	 			1 310	CER1	ST	D C	ERT	STD	CERT	STD	CERT	STD
		@ 50K	0.008		0.040	0.5	1.7	0.003	0.0	5	0.3	8	*	*	0.003	0.07
		@ UL	0.009	*	0.055	0.6	2.1	0.003	0.0	7	1.0	11	•	*	0.004	0.09
	@ 5	50°F & 4K	0.019	•	0.080	0.7	1.7	0.02	0.0	5	0.5	16		*	*	*
CO @ 20°F	[g/mi] = & 50k	ァ陽 Li	TP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) TP 2 = @ UL (Tier 1, TLEV)		NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
		10.112	- (E) OF (116)	323	CERT	STD	CERT	STD	CERT	STD	CER	TST			CERT	STD
CERT	2.9			SFTP 1	*	*	*		0.01	0.14	2.6	8.0	0.003	0.20	0.6	2.7
STD	10.0			SFTP 2	*	•	*	•	•		•		*	0.20	0.6	2.7
@ UL		EVAPORA	TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2				FVΔ	PORATI	IVE FAM			/ADOD 4 7		
	3-D	2-[RL	ORVR	3-D	2-D	RL	ORVR						VAPORATI	VE FAMIL	_Y 4
CERT	1.0	1.9		0.07	0.45	0.27	0.01	0.06	3-D	2-D	RL	ORVE		2-D	RL	ORVR
STD	2.0	2.5		0.20	0.65	0.85	0.05		-		<u> </u>	*	*	•	*	•
				7.20	0.00	0.00	0.05	0.20	•	•	*	*	*	•		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That certification to the evaporative emission standards in 13 CCR 1976(b)(1)(B)-(C) listed above has been permitted pursuant to 13 CCR 1976(b)(1)(F)-Endnote 3(b).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of September 2005.

Allen Lyons, Chief

Mobile Source Operations Division