



Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFUL LIFE (miles)		INTERMEDIATE IN-USE COMPLIANCE (*N/A or full in-use; A/E=exh. / evap. intermediate in-use)		FUEL TYPE
				EXH / ORVR	EVAP	EXH	EVAP	
2006	6GMXB03.9146	PC & LDT ≤ 6,000 pounds GVW (PC; LDT 3,751-5,750 pounds LVW)	"LEV II" Low Emission Vehicle (LEV II LEV)	120K	150K	A	E	Gasoline (Tier 2 Unleaded)
No.	ECS & SPECIAL FEATURES		EVAPORATIVE FAMILY (EVAF)		DISPLACEMENT (L)			
1	2TWC, 2HO2S(2), SFI, EGR, OBD(F)		6GMXR0117809		3.4, 3.5, 3.9			
2	TWC, HO2S(2), SFI, EGR, OBD(F)		6GMXR0133810					
*	*		6GMXR0133813					
*	*		6GMXR0203958					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1295 dated March 18, 2005.

Executed at El Monte, California on this 16th day of May 2005.

Allen Lyons
Allen Lyons, Chief
Mobile Source Operations Division

SUPERSEDED

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF=* CH4 RAF = *		NMOG or NMHC STD [g/mi]	CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram ml=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure											
STD-PC	STD-LDT2	NMOG CERT [g/mi]	NMHC CERT [g/mi]		CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]			
0.046	0.062				CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		
	@ 50K	0.038	*	0.075	1.4	3.4	0.04	0.05	*	15.	*	*	0.02	0.07		
	@ UL	0.045	*	0.090	1.5	4.2	0.05	0.07	*	18.	*	*	0.04	0.09		
	@ 50°F & 4K	0.074	*	0.150	1.5	3.4	0.01	0.05	*	30.	*	*	*	*		

CO [g/mi] @ 20°F & 50K	SFTP @ 4000 miles	SFTP @ * miles	NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT 5.8			*	*	*	*	0.05	0.14	6.2	8.0	0.01	0.20	2.1	2.7
STD 10.0			*	*	*	*	*	*	*	*	*	*	*	*

Evaporative Family	3-Days Diurnal + Hot Soak (grams/test) @ UL		2-Days Diurnal + Hot Soak (grams/test) @ UL		Running Loss (grams/mile) @ UL		On-Board Refueling Vapor Recovery (grams/gallon) @ UL	
	CERT	STD	CERT	STD	CERT	STD	CERT	STD
6GMXR0117809	0.53	0.65	0.70	0.85	0.00	0.05	0.04	0.20
6GMXR0133810	0.22	0.50	0.18	0.85	0.00	0.05	0.01	0.20
6GMXR0133813	0.53	0.85	0.70	0.85	0.00	0.05	0.04	0.20
6GMXR0203958	0.58	0.65	0.47	0.85	0.00	0.05	0.14	0.20

* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TB|=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2006 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP		
BUICK	RENDEZVOUS AWD	6GMXR0133813	2	3.5	A	E	SFTP	Full
BUICK	RENDEZVOUS FWD	6GMXR0133813	2	3.5	A	E	SFTP	Full
BUICK	TERRAZA AWD	6GMXR0203958	2	3.5	A	E	SFTP	Full
BUICK	TERRAZA FWD	6GMXR0203958	2	3.9	A	E	SFTP	Full
BUICK	TERRAZA FWD	6GMXR0203958	2	3.5	A	E	SFTP	Full
CHEVROLET	EQUINOX AWD	6GMXR0117809	2	3.4	A	E	SFTP	Full
CHEVROLET	EQUINOX FWD	6GMXR0117809	2	3.4	A	E	SFTP	Full
CHEVROLET	MALIBU	6GMXR0133810	1	3.5	A	E	SFTP	Full
CHEVROLET	MALIBU MAXX	6GMXR0133810	1	3.5	A	E	SFTP	Full
CHEVROLET	UPLANDER AWD	6GMXR0203958	2	3.5	A	E	SFTP	Full
CHEVROLET	UPLANDER FWD	6GMXR0203958	2	3.5	A	E	SFTP	Full
CHEVROLET	UPLANDER FWD	6GMXR0203958	2	3.9	A	E	SFTP	Full
PONTIAC	G6	6GMXR0133810	1	3.5	A	E	SFTP	Full
PONTIAC	G6	6GMXR0133810	1	3.9	A	E	SFTP	Full
PONTIAC	G6 GT/GTP CONVERTIBLE	6GMXR0133810	1	3.5	A	E	SFTP	Full
PONTIAC	G6 GT/GTP CONVERTIBLE	6GMXR0133810	1	3.9	A	E	SFTP	Full



California Environmental Protection Agency

AIR RESOURCES BOARD

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1295-1

**New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles**

PONTIAC	MONTANA SV6 AWD	6GMXR0203958	2	3.5	A	E	SFTP	Full
PONTIAC	MONTANA SV6 FWD	6GMXR0203958	2	3.5	A	E	SFTP	Full
PONTIAC	MONTANA SV6 FWD	6GMXR0203958	2	3.9	A	E	SFTP	Full
PONTIAC	TORRENT AWD	6GMXR0117809	2	3.4	A	E	SFTP	Full
PONTIAC	TORRENT FWD	6GMXR0117809	2	3.4	A	E	SFTP	Full
SATURN	RELAY AWD	6GMXR0203958	2	3.5	A	E	SFTP	Full
SATURN	RELAY FWD	6GMXR0203958	2	3.5	A	E	SFTP	Full
SATURN	RELAY FWD	6GMXR0203958	2	3.9	A	E	SFTP	Full
CHEVROLET	MALIBU	6GMXR0133810	1	3.9	A	E	SFTP	Full
CHEVROLET	MALIBU MAXX	6GMXR0133810	1	3.9	A	E	SFTP	Full

SUPERSEDED