GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1292-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN- COMP (*=N/A or A/E=ex	MEDIATÉ USE LIANCE full in-use; h. / evap. iate in-use)	FUEL TYPE	
		.	"LEV II" Super Ultra Low Emission Vehicle (LEV II	EXH / ORVR	EVAP	EXH	EVAP	Gasoline	
2006	6GMXV03.8044	Passenger Car	SULEV)	150K	150K	A	E	new tree	
No.	ECS & SI	PECIAL FEATURES	EVAPORATIVE FAMILY (EVAF) DISPLACEMENT (L)						
1	TWC, HO2S(2)	, SFI, EGR, AIR, OBD(F)	6GMX	6GMXR0133890					
*			8GMX	R0133891		3.8			
*		*		*		0.0			
•		*		•					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50⁰ Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

That additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1292 dated March 21, 2005.

Executed at El Monte, California on this ______ day of April 2005.

Allen Lyons, Chief

Mobile Source Operations Division



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *		NMOG or	CH4=melhane: NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCH0=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram										
CERT	STD	NMOG	NMHC	NMHC STD	mi=mile; K	=1000 miles:	F≃degrees	Fahrenheit; S	FTP=suppler	mental federa	il test procedu	ire		
		CERT	CERT	_	COL	a/mi]	NOx	[g/mi]	HCHO	[mg/ml]	PM [g/mi]	Hwy NO	x [g/mi]
0.048	0.046	[g/ml]	[g/ml]	[g/mi]	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
19 (01)	@ 50K	*	*	*	*	*	•	*	*	*	*	*	*	*
	@ UL	0.006	*	0.010	0.2	1.0	0.01	0.02	•	4.	*	*	0.004	0,03
7 7 1 Q	50°F & 4K	*	*	*	*	*	*	*	•	*	*	*	*	•
	i i	2	Part of	NMHC+NO	Ox [g/mi]	CO (g	/mi]	NMHC+N	Ox	CO [g/mi]		HC+NOx	CO	g/mi]

c	O [g/mi]			(comp			osite)	[g/mi]		เบร		[g/ml]	[SC03]	[sc	03]
	0°F & 50K			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	3.8	SFTP @ 4000	miles	+	*	*	*	0.01	0.14	0.4	8.0	0.02	0.20	0.2	2.7
STD	10.0	SFTP @ *	miles	*	*	*	*	*	*	*	*	*	*	*	*
	L		Davis Div	ملا بامست	4 Cook	2 Dave Di	urnal + H	ot Soak	F	Zunning L	220		n-Board	Refueling V	apor

Evaporative Family	3-Days Diurnal + Hot Soak (grams/test) @ UL		2-Days Diurn (grams/te	al + Hot Soak est) @ UL	Runnin (grams/m	ig Loss iile) @ UL	On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
6GMXR0133890	0,22	0.50	0.18	0.65	0.00	0.05	0.01	0.20	
6GMXR0133891	0.32	0.50	0.28	0.65	00.0	0.05	0.01	0.20	
*	+		*	*	*	*	*	*	
*	*	*	*	*		*	*	*	

^{* =} not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=surer ULEV; SULEV=surer ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AlR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttie body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2006 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full in-use; h. / evap. late in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
BUICK	ALLURE	6GMXR0133891	1	3.8	Α	E	SFTP	Full
BUICK	LACROSSE	6GMXR0133891	1	3.8	Α	E	SFTP	Full
PONTIAC	GRAND PRIX	6GMXR0133891	1	3.8	A	E	SFTP	Full
BUICK	ALLURE	6GMXR0133890	1	3.8	Α	E	SFTP	Full
BUICK	LACROSSE	6GMXR0133890	1	3.8	A	E	SFTP	Full
PONTIAC	GRAND PRIX	6GMXR0133890	1	3,8	Α	E	SFTP	Full