

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA	R	TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW) LDT: 6001-8500 Pounds GVW; 3751-5750 LVW	STANDAF (LEV=low emi- transitional L SULEV	ST EMISSION RD CATEGORY ssion vehicle; TLEV= EV; ULEV=ultra LEV; =super ULEV) EV II LEV	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles) EXH/ORVR: 120K EVAP: 150K	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas) Gasoline (Tier 2 Unleaded)			
No. 1 2	FAI	EVAPORATIVE FAMILY (EVAF) EVWXR0230275			No. 1 2	SPECIAL FEATURES EMISSION CONTROL SYST 2WU-TWC, TWC, 2HC	EMS (ECS)	*= not applicable OBD (P)	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O25/HO2S=oxygen sensor/heated O25 AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIRI/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
3 4		*		5 m	4		*						
EVA No.		ECS No.	ENGI SIZE 3.2	<u>(L)</u>			EHICLES SUBJ FANDARDS AR	9					
					-								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/ml]			NMOG @ RAF= * CH4 RAF = *			NMOG or NMHC	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day disurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refuelling vapor recovery g=gram memorality regular k=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure										
CERT		STD	NMOG CERT [g/mi]		NMHC CERT	STD [g/mi]	mg=milligr	a <u>m mi≕</u> [g/mi]	1000 miles F=degrees i Ox [g/mi] HCHO				PM [g/mi]		Hwy NOx [g/mi]		
0.075	0	.062			[g/mi]		CERT	STD	CERT			RT	STD	CERT	STD	CERT	STD
3.4.36.7	@ 50K		0.0	40	*	0.075	0.6	3.4	0.03	0.05	5 *		15	*	*	0,02	0.07
	@ UL				0.090	0.7	4.2	0.03	0.07		*	18	*	*	0.03	0.09	
	€ 50°	F & 4K		91	*	0.150	1.1	3.4	0.03	0.05		*	30	•	*	*	*
CO [g/mi]	SFTP 1 = @ 4K (SULEV, ULEV,				NMHC+NC		CO [g/mi] (composite)		NMHC [g/mi] [CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
	@ 20°F & 50K		LEV) or 50K (Tier 1, TLEV SFTP 2 = @ UL		r 1, ILEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	CERT	STD	CERT	STD
CERT	2.0	VIII.			SFTP 1	•	•	*	*	0.06	0.60	5.1	B 11.	8 0.06	0.44	0.7	4.0
STD	12.5				SFTP 2	*	+	*	•	*	•	*	*	*	*	*	•
						PORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4				
@ UL	3-D	2-1		RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR
CERT	0.66			0.002	0.02	+	*	•	*	•	*	•	*	*	*	*	*
STD	0.90	_		0.05	0,20	+ +	*	*	•	•	*	*	*	*	*		*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _______ day of June 2005.

Allen Lyans, Chief Mobile Source Operations Division